

submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator
MERIDIAN OIL

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
1227' FNL', 1090' FEL, Sec.18, T-32-N, R-9-W, NMPM
A

5. Lease Number
SF-078513

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

San Juan 32-9 Unit

8. Well Name & Number
San Juan 32-9 U #77

9. API Well No.
30-045-11465

10. Field and Pool
Blanco Mesaverde

11. County and State
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission	Type of Action	
☐ Notice of Intent	☒ Abandonment	☐ Change of Plans
☒ Subsequent Report	☐ Recompletion	☐ New Construction
☐ Final Abandonment	☐ Plugging Back	☐ Non-Routine Fracturing
	☐ Casing Repair	☐ Water Shut off
	☐ Altering Casing	☐ Conversion to Injection
	☐ Other -	

13. Describe Proposed or Completed Operations

8-29-96 MIRU. ND WH. NU BOP. TOOHO w/189 jts 2 3/8" tbq. TIH w/5 1/2" gauge ring to 5860 TOOH. TIH w/5 1/2" BP, set @ 5850'. TOOHO. SD for holiday.

9-3-96 TIH, tag BP @ 5850'. Load hole & circ hole clean w/110 bbl wtr. PT csg to 500 psi, failed. Plug #1: pump 17 sx Class "B" cmt into Mesaverde perfs @ 5700-5850'. TOOHO to 5248'. Plug #2: pump 18 sx Class "B" cmt inside csg @ 5089-5248'. TOOHO to 3999'. Plug #3: pump 42 sx Class "B" cmt inside csg @ 3728-3999'. TOOHO to 3655'. Plug #4: pump 39 sx Class "B" cmt inside csg @ 3481-3655'. TOOHO to 3248'. Plug #5: pump 37 sx Class "B" cmt inside csg @ 3083-3248'. TOOHO. TIH w/7 5/8" gauge ring to 2050'. TOOHO. TIH, perf 3 sqz holes @ 2060'. TOOHO. TIH w/7 5/8" cmt retainer, set @ 2000'. TOOHO. TIH. SDON.

9-4-96 Load hole w/23 bbl wtr. PT csg, failed. Establish injection. Plug #6: pump 82 sx Class "B" cmt outside 7 5/8" csg below cmt retainer @ 1872-2060'. Pump 40 sx Class "B" cmt on top of cmt retainer. TOOHO. WOC. TIH, tag TOC @ 1819'. TOOHO. TIH. Perf 3 sqz holes @ 760'. TOOHO. TIH W/7 5/8" cmt retainer, set @ 719'. Load hole w/wtr. PT csg to 500 psi/5 min, OK. Establish injection. Plug #7: pump 46 sx Class "B" cmt outside 7 5/8" csg below cmt retainer @ 660-760'. Pump 25 sx Class "B" cmt on top of cmt retainer to 608'. TOOHO. TIH, perf 3 sqz holes @ 345'. TOOHO. Establish circ down csg & out bradenhead w/38 bbl wtr. Plug #8: pump 178 sx Class "B" cmt down csg & out bradenhead. Circ 1 bbl cmt to surface. ND BOP. Cut off WH. Pump 10 sx Class "B" cmt down 7 5/8" csg. Pump 4 sx Class "B" cmt down 7 5/8" x 10 3/4" annulus. Install dry hole marke w/11 sx Class "B" cmt. RD. Rig released. Well plugged and abandoned 9-4-96.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Administrator Date 9/17/96

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any:

APPROVED

SEP 24 1996

WMOCD