

(SUBMIT IN TRIPLICATE)

Indian Agency

Ute Mountain Tribal

Allottee

Lease No. 14-20-604-121

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

RECEIVED  
DEC 1 1959

U. S. GEOLOGICAL SURVEY  
FARMINGTON, NEW MEXICO

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Ute Mountain Tribal "F"

Farmington, New Mexico November 30, 1959

Well No. 3 is located 2310 ft. from <sup>[N]</sup><sub>[S]</sub> line and 1980 ft. from <sup>[E]</sup><sub>[W]</sub> line of sec. 28NW/4 of Section 28  
(1/4 Sec. and Sec. No.)T-31-N  
(Twp.)R-14-W  
(Range)N.M.P.M.  
(Meridian)Verde Gallup  
(Field)San Juan  
(County or Subdivision)New Mexico  
(State or Territory)

The elevation of the derrick floor above sea level is 5933 ft. (RDB)

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

TD 3687'. 5-1/2" casing was set at 3682' with 2 stage cement collar at 3389'. Cemented first stage with 60 sacks 6% gel cement containing 2 pounds Tuf-plug per sack. Tested casing with 3000 psi for 30 minutes, which held with no indication of pressure drop. Opened cement to circulate between stages. Circulated trace of cement. Cemented second stage with 350 sacks 6% gel cement containing 2 pounds Tuf-plug per sack. Tested casing with 3000 psi which held with no indication of pressure drop. Drilled 2 stage collar to 3687'. Displaced mud with oil. Released rotary rig on November 27, 1959. Top of cement by Temperature Survey 2100'.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be conducted.

Company Pan American Petroleum Corporation

Address Box 487

Farmington, New Mexico

Attention: L. O. Spear, Jr.

ORIGINAL SIGNED BY

By R. M. Bauer, Jr.

Title Area Engineer