UNITED STATES DEPARTMENT OF THE INTERIOR (Other Instructions on re-

GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE.

Form approved. Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND RERIAL NO.

SE 078472

	1 01 070472
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
LL GAS X OTHER	7. UNIT AGREEMENT NAME San Juan 32-7 Unit
4E OF OPERATOR	8. FARM OR LEASE NAME
El Paso Natural Gas Company	San Juan 32-7 Unit
RESS OF OPERATOR	9. WELL NO.
PO Box 990, Farmington, NM 87401	34

LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) 10. FIELD AND POOL, OR WILDCAT At surface 1080'N, 1190'E <u>Basin Dakota</u> 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 27, T-32-N, R-7-W

NMPM 12. COUNTY OR PARISH | 13. STATE 14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6600'GL San Juan NM

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:							
TEST WATER SHUT-OFF		PULL OR ALTER CASING MULTIPLE COMPLETE		WATER SHUT-OFF FRACTURE TREATMENT	$\frac{X}{X}$		REPAIRING V		
SHOOT OR ACIDIZE		ABANDON*		SHOOTING OR ACIDIZING		· .	ABANDONME	NT*	·
REPAIR WELL	<u></u>	CHANGE PLANS		(Other) (Note: Report res	ulta of	multiple	aompletion	on Wel	
(Other)	_		<u> </u>	Completion or Reco	mpleti	on Repor	t and Log for	m.)	

- 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*
 - TD 3774'. Ran 121 joints 7", 20#, KE intermediate casing, 3762' set at 3774'. 10-12-73 Cemented with 272 cu.ft. cement. WOC 12 hours, held 1200#/30 min. of cement at 1600'.
 - 10-17-73 TD 8243'. Ran 273 joints 4 1/2", 11.6 and 10.5#, KS production casing, 8231 set at 8243'. Float collar set at 8234'. Cemented with 690 cu.ft. cement. WOC 18 hours. Top of cement at 4700'. **最高的**多年
 - PBTD 8234'. Tested casing to 4000#-OK. Perf'd 8110', 8120', 8161', 8170', 10-19-73 8172', 8184' and 8208' with one shot per zone. Frac'd with 52,626 gallons treated water and 50,000# 40/60 sand, no ball drops. Flushed with 5502 gallons water.

18. I hereby certify that the foregoing is true and correct

Drilling Clerk DATE October 30, 1973 (This space for Federal or State office use) 5 ≠ ± ² DATE APPROVED BY CONDITIONS OF APPROVAL, IF ANY: