

**UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY**

SUBMIT IN TRIPPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

MOO-C-1420-1720
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

Ute Mountain Tribe
7. UNIT AGREEMENT NAME

S. FARM OR LEASE NAME

Ute Mountain Tribe

9. WELL NO.

14-1

10. FIELD AND POOL, OR WILDCAT

Verde Gallup

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 14, T31N, R15W

12. COUNTY OR PARISH 13. STATE

San Juan N. Mexico

1. OIL WELL GAS WELL OTHER Dry

2. NAME OF OPERATOR
R. L. Burns Corp.

3. ADDRESS OF OPERATOR
3990 First National Bank Building, Dallas, Texas 75202

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

765' FEL & 2150' FNL, Sec. 14, T31N, R15W

14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5859' gr.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
(Other)

PULL OR ALTER CASING
MULTIPLE COMPLETE
ABANDON*
CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
(Other)

REPAIRING WELL
ALTERING CASING
ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Perforated @ 2420, 2423, 2425, 2429, 2443, 2445, 2503, 2505, 2518 with 2 shots per ft.

Acidized and fractured with 200 gal. 15% acid, 26,730 gal. diesel oil, 58,200# 20/40 sand.

Plugged to abandon as follows:

Plug #1 2630-2348' 30sx.
Plug #2 1300-1133' 20sx.
Plug #3 855- 691' 30sx.
Plug #4 55- 0' 10sx.
Plug #5 8sx. between 9-5/8" csg. and 7" csg.

Welded on plate and dry hole marker.

PxA 9-24-75

RECEIVED
OCT 6 1975
GEOLOGICAL SURVEY

18. I hereby certify that the foregoing is true and correct

SIGNED *[Signature]*

TITLE Engineer

DATE 10-1-75

(This space for Federal or State office use)

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY: