

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

MOO-C-1420-1720

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Ute Mountain Tribe

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Ute Mountain Tribe

9. WELL NO.

14-1

10. FIELD AND POOL, OR WILDCAT

Verde Gallup

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 14, T31N, R15W

12. COUNTY OR PARISH

San Juan

13. STATE

N. Mexico

1. OIL WELL ☐ GAS WELL ☒ OTHER Dry

2. NAME OF OPERATOR

R. L. Burns Corp.

3. ADDRESS OF OPERATOR

3990 First National Bank Building, Dallas, Texas 75202

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

765' FEL & 2150' FNL, Sec. 14, T31N, R15W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5859' gr.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Perforated @ 2420, 2423, 2425, 2429, 2443, 2445, 2503, 2505, 2518 with 2 shots per ft.

Acidized and fractured with 200 gal. 15% acid, 26,730 gal. diesel oil, 58,200# 20/40 sand.

Plugged to abandon as follows:

Plug #1 2630-2348' 30sx.

Plug #2 1300-1133' 20sx.

Plug #3 855- 691' 30sx.

Plug #4 55- 0' 10sx.

Plug #5 8sx. between 9-5/8" csg. and 7" csg.

Welded on plate and dry hole marker.

PRA 9-24-75

RECEIVED

FEB 28 1984

OIL CON. DIV.

DIST. 3

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Engineer

DATE 10-1-75

(This space for Federal or State office use)

APPROVED BY

David J. Miller

TITLE

Area Manager

DATE

FEB 24 1984

CONDITIONS OF APPROVAL, IF ANY:

S. N. M. C. D.

*See Instructions on Reverse Side