

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF078604

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Scott

9. WELL NO.

10

10. FIELD AND POOL, OR WILDCAT

Undes. PC

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREASec. 4, T-31-N, R-10-W  
N.M.P.M.

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT--" for such proposals.)1. OIL ☐ GAS ☒  
WELL WELL OTHER

2. NAME OF OPERATOR

El Paso Natural Gas Company

3. ADDRESS OF OPERATOR

P. O. Box 990, Farmington, NM 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

800'S, 1000'W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5961' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any  
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-  
nent to this work.)\*08-21-75 TD 2957'. Ran 93 joints 2 7/8", 6.4#, J-55 production casing, 2946' set at  
2957'. Baffle set at 2946'. Cemented with 771 cu. ft. cement. WOC 18  
hours. Top of cement at 750'.09-16-75 Tested casing to 4000#--OK.  
PBSD 2946'. Perf'd 2765', 2770', 2779', 2783', 2822', 2828', for a total  
of 6 holes. Frac'd with 41,000#--20/40 sand and 41,000 gallons treated  
water. Dropped no balls. Flushed with 714 gallons water.

RECEIVED

SEP 26 1975

U. S. GEOLOGICAL SURVEY

18. I hereby certify that the foregoing is true and correct

SIGNED

*A. P. Dices*

TITLE Drilling Clerk

DATE September 19, 1975

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE