

**UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY**

SUBMIT IN DUPLICATE*

(See other In-
structions on
reverse side)Form approved,
Budget Bureau No. 42-R355.5.

5. LEASE DESIGNATION AND SERIAL NO.

NM 03190

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Cox Canyon Unit

8. FARM OR LEASE NAME

Cox Canyon Unit

9. WELL NO.

8A

10. FIELD AND POOL, OR WILDCAT

Blanco Mesa Verde

11. SEC., T., R., M., OR BLOCK AND SURVEY
OR AREA

Sec. 17, T32N, R11W

12. COUNTY OR
PARISH
San Juan13. STATE
NM

1a. TYPE OF WELL:

OIL WELL ☐GAS WELL ☒DRY ☐

Other

b. TYPE OF COMPLETION:

NEW WELL ☒WORK OVER ☐DEEP-EN ☐PLUG BACK ☐DIFF. RESVR. ☐

Other

2. NAME OF OPERATOR

Northwest Pipeline Corporation

3. ADDRESS OF OPERATOR

P.O. Box 90, Farmington, New Mexico 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface 1850' FNL & 660' FEL

At top prod. interval reported below

As above

At total depth As above

14. PERMIT NO.

DATE ISSUED

15. DATE SPUDDED

8-5-76

16. DATE T.D. REACHED

8-12-76

17. DATE COMPL. (Ready to prod.)

9-1-76

18. ELEVATIONS (DF, RKB, RT, GR, ETC.)*

6693' GR

19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD

5921'

21. PLUG, BACK T.D., MD & TVD

5877'

22. IF MULTIPLE COMPL.,
HOW MANY*23. INTERVALS
DRILLED BY

ROTARY TOOLS

CABLE TOOLS

ALL

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)

5162' - 5810' Mesa Verde

RECEIVED

25. WAS DIRECTIONAL
SURVEY MADE

No

26. TYPE ELECTRIC AND OTHER LOGS RUN

Gamma Ray Induction and Density

SEP 10 1976

27. WAS WELL CORED

No

28. CASING RECORD (Report on string casing)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULPED
9 5/8"	40	220'	12 1/4"	115 sks.	
7"	20	3762'	8 3/4"	240 sks.	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
4 1/2"	3620'	5921'	220		2 3/8"	5857'	None

31. PERFORATION RECORD (Interval, size and number)

One shot at:

5162', 5232', 5238', 5246', 5266', 5272',
5280', 5300', 5372', 5381', 5421', 5496',
5656', 5664', 5672', 5680', 5688', 5694',
5700', 5706', 5736', 5742', 5748', & 5810'.

Size 0.32" holes

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
5162' - 5810'	1500 gal. 7 1/2% HCl w/30 ball sealers. Fraced w/70,000 gal. water and 60,000# 20/40 sand.

33.* PRODUCTION

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)				WELL STATUS (Producing or shut-in)	
		Flowing				Shut-in	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO
9-1-76	3	3/4	→	4391			
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)	
467 PSIG	768 PSIG	→		17,051			

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

TEST WITNESSED BY

Waiting on pipeline connection

35. LIST OF ATTACHMENTS

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

D. H. Maroncelli

TITLE Production Engineer

DATE 9-13-76

*(See Instructions and Spaces for Additional Data on Reverse Side)

DHM/ks

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 23, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 13: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.

Items 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 27: *Stacks Comment*: Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES:				38. GEOLOGIC MARKERS		
SHOW AND INDICATE ZONES OF POROSITY AND CONTENTS THEREOF: CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES						
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	MEAS. DEPTH	TRUE VERT. DEPTH
Mesa Verde	5155'		SS. Buff to light gry., silty in part, fine to medium grained, interbedded with siltstone, shale and coal.	Ojo Alamo Kirtland Fruitland Pictured Cliffs Lewis Cliff House Menefee Point Lookout T.D.	2259' 2499' 3139' 3357' 3562' 5155' 5306' 5652' 5921'	Same " " " " " " " "