

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

14-20-603-734

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Navajo

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR		Horseshoe Gallup Unit
Atlantic Richfield Company		8. FARM OR LEASE NAME
3. ADDRESS OF OPERATOR		Horseshoe Gallup Unit
501 Lincoln Tower Bldg., 1860 Lincoln St., Denver, Colo. 80203		9. WELL NO.
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface		295
Unit "A" (NE NE) 50' f/North & 50' f/East lines Sec. 31		10. FIELD AND POOL, OR WILDCAT
API #30-045-22100		Horseshoe Gallup
14. PERMIT NO.		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Mr. P. T. McGrath 6/7/76		Sec. 31-31N-16W
15. ELEVATIONS (Show whether DF, RT, GR, etc.)		12. COUNTY OR PARISH
5430' GL; 5441' KB		San Juan
		13. STATE
		New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐

PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) ☒

REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☐

Spud & set surface casing ☒
(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

MI & RU. Spudded 12-1/4" hole 5 p.m. 8/1/76. Drld 12-1/4" hole to 135'.
Ran 3 jts, 118.33', 8-5/8" OD 24# K-55 ST&E N casing, set at 132.23' KB, cemented
w/ 120 ex Class "B" w/ 2% CaCl, plug down 12:15 a.m. 8/2/76. WOC.

Nippled up, installed BOP. Tested blind & pipe rams to 800# f/ 30 min., held O.K.
started drilling out 6:45 p.m. 8/2/76.

8/3/76 Drilling ahead @ 730'. 7-7/8" hole.

RECEIVED

AUG 6 1976

U.S. GEOLOGICAL SURVEY

18. I hereby certify that the foregoing is true and correct

SIGNED

W. A. Walther, Jr.
W. A. Walther, Jr.

TITLE

Operations Manager

DATE

8/3/76

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: