

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. 14-20-603-2037
2. NAME OF OPERATOR Atlantic Richfield Company		6. IF INDIAN, ALLOTTEE OR TRIBE NAME Navajo
3. ADDRESS OF OPERATOR 501 Lincoln Tower Bldg., 1860 Lincoln St., Denver, Colo. 80203		7. UNIT AGREEMENT NAME Horseshoe Gallup Unit
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface Unit "J" (NW SE) - 2474' f/South & 2463' f/East lines Sec. 24 API #30-045-22103		8. FARM OR LEASE NAME Horseshoe Gallup Unit
14. PERMIT NO. Mr. McGrath 6/7/76		9. WELL NO. 292
15. ELEVATIONS (Show whether DF, RT, CR, etc.) 5707' 3L, 5718' KB		10. FIELD AND POOL, OR WILDCAT Horseshoe Gallup
		11. SEC. T., R., M., OR BLK. AND SURVEY OR AREA Sec. 24-31N-17W
		12. COUNTY OR PARISH San Juan
		13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) **Spud & set surf. casing** ☒REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

MI & RU rotary. Spud 12-1/4" hole 1:15 p.m. 7/21/76. Drld 12-1/4" hole to 131'. Ran 3 jts, 114.40', 8-5/8" OD 24# K-55 8rd ST&C N casing, set at 127.40' KB, cemented w/ 120 sx Class "B" cmt w/ 2% CaCl₂, good cmt returns, plug down 12:45 a.m. 7/22/76. WOC.

Nippled up, instl'd BOP. Test BOP & casing to 800# f/ 30 min, held O.K.. Tag cmt @ 90', started drlg cmt 6:45 p.m. 7/22/76.

7/23/76 - Drilling ahead @ 775'. 7-7/8" hole.



RECEIVED

JUL 26 1976

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

18. I hereby certify that the foregoing is true and correct

SIGNED

W. A. Walther, Jr.TITLE Operations ManagerDATE 7/23/76

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: