

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF-078040A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Southland Royalty Company

3. ADDRESS OF OPERATOR

P.O. Box 570, Farmington, New Mexico 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

790' FSL & 1070' FEL

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Childers

9. WELL NO.

#1-A

10. FIELD AND POOL, OR WILDCAT
Blanco Pictured Cliffs
Blanco Mesa Verde11. SEC., T., E., M., OR BLK. AND
SURVEY OR AREA

Section 1, T31N, R11W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6050' GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

1. Pull tubing.
2. Set Baker model "F" packer with knock out plug @ 3090'.
3. Perforate Pictured Cliffs from 2811' to 2885' with 9 holes.
4. Frac Pictured Cliffs with 79,400 gallons of water and 74,400# of 20/40 sand.
5. Clean out with air to packer and knock out expendable plug.
6. Land 2 1/16" tubing @ 5332' with seal assembly in packer @ 3090'.
7. Land 1 1/4", IJ, tubing @ 2820'.
8. Nipple up dual wellhead.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE District Production Manager

DATE 9-7-78

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

kde

*See Instructions on Reverse Side

NMOC