						/	
Form 9-331 (May 1963)				SUBMIT IN TRIPLICATE• (Other instructions on re-	re- 5. LEASE DESIGNATION AND SERIAL NO. SF-077648		
		GEOLOGICAL SURVEY					
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)					6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
1.	Use ArrLio.	ATION FOR FERMIT		Sans. /	7. UNIT AGREEMENT N	AME	
OIL GAS WELL WEI	L X OTHER						
2. NAME OF OPERATO		8. FARM OR LEASE NAME					
Aztec Oil	& Gas Compa	Davis					
3. ADDRESS OF OPERATOR					9. WELL NO.		
P. O. Drawer 570, Farmington, New Mexico 87401 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1670' FSL & 1100' FWL					#1-A		
					10. FIELD AND POOL, OR WILDCAT		
					Blanco Mesa Verde		
		11. SEC., T., R., M., OR BLK. AND SURVEY OR ABEA					
					Section 11,	T31N, R12W	
14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)			, GR, etc.)	12. COUNTY OR PARIS	-		
		6282' GR			New Mexico		
16.	Check A			ure of Notice, Report, or C	Other Data		
					UENT REPORT OF:		
TEST WATER SHUT-OFF PULL OR ALTER CASING WATER SHUT-OFF					REPAIRING WELL		
FRACTURE TREAT		MULTIPLE COMPLETE		FRACTURE TREATMENT	ALTERING	CASING	
SHOOT OR ACIDIZ		ABANDON*		SHOOTING OR ACIDIZING	ABANDONM	ENT*	
REPAIR WELL	REPAIR WELL CHANGE PLANS (Other)(CASING REPORT X	
(Other)				Completion or Recomp	s of multiple completion letion Report and Log f	orm.)	
17. DESCRIBE PROPOS proposed work nent to this wo	. If well is direct	ERATIONS (Clearly state ionally drilled, give sub	all pertinent d surface location	etails, and give pertinent dates s and measured and true vertic	, including estimated de al depths for all marke	ate of starting any ers and zones perti-	
10-27-76	-76 Ran 113 jts of 7", 20#, K-55, 8rd casing. Total 4906.26', shoe set at 4917', float collar at 4837', stage collar at 2920'. Cmt 1st stage with 75 sacks Class B. Plug down 1:30 PM. Cemented 2nd stage with 175 sacks Class B. Plug down at 5:30 PM.						
10-31-76	10-31-76 Ran 21 jts of 4-1/2", 10.50#, H-40, 8rd casing. Total 696.72', shoe set at 5464', float collar at 5463', liner hanger at 4761'. Cemented with 55 sacks Class B. Plug down at 2:15 PM.					hoe nted	
			NOTE OTE		NOV 4 197		

18. I hereby certify that the foregoing is true and correct SIGNED	TITLE District Production Manager	DATE November 3, 1976
(This space for Federal or State office use)		
APPROVED BY	TITLE	DATE

APPROVED BY ______ CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side