

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease
State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator <b>AMOCO PRODUCTION COMPANY</b>	8. Farm or Lease Name <b>Leeper Gas Com "B"</b>
3. Address of Operator <b>501 Airport Drive, Farmington, New Mexico 87401</b>	9. Well No. <b>1</b>
4. Location of Well UNIT LETTER <b>C</b> , <b>1110</b> FEET FROM THE <b>North</b> LINE AND <b>1450</b> FEET FROM THE <b>West</b> LINE, SECTION <b>34</b> TOWNSHIP <b>32</b> RANGE <b>10</b> NMPM.	10. Field and Pool, or Wildcat <b>Blanco Pictured Cliffs</b>
15. Elevation (Show whether DF, RT, GR, etc.) <b>5882' GL</b>	12. County <b>San Juan</b>

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <b>Set casing</b> <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 12-1/4" hole 12-12-76 and drilled to 257'. Drilled boulders from 25' to 95'. Set 8-5/8" casing at 257' on 12-13-76. Pumped 10 barrels chemical wash ahead of 200 sacks Class "B" cement with 2% CaCl<sub>2</sub>. Circulated cement. WOC and tested blowout preventer to 400 psi OK. Reduced hole to 7-7/8" and continued drilling.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED A. R. Kendrick TITLE Area Adm. Supvr. DATE December 17, 1976

Original Signed by A. R. Kendrick

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: