

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR
AMOCO PRODUCTION COMPANY

3. ADDRESS OF OPERATOR
501 Airport Drive Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
370' FNL x 445' FEL, Section 5,
AT SURFACE: T-31-N, R-10-W
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>

(other) Spud & Set Casing

5. LEASE

SF-078215 B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

McEwen Gas Com "B"

9. WELL NO.

10. FIELD OR WILDCAT NAME

Blanco Pictured Cliffs

11. SEC., T., R., M., OR BLK. AND SURVEY OR
AREA NW/4 NW/4 Section 5,
T-31-N, R-10-W

12. COUNTY OR PARISH 13. STATE
San Juan NM

14. API NO.

30-045-22205

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6064' EGL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 12-1/4" hole on 3/10/78. Drilled to 277'. Set 8-5/8" 24# K-55 casing at 277'. Cemented with 250 sx Class "B" with 2% CaCl₂. Circulated good cement. Pressure tested to 500 psi for 30 minutes; held OK.

Drilled 7-7/8" hole to a total depth of 3098'. Ran 4-1/2" 10.5# casing; set at 3098'. Cemented with 710 sx Class "B" 50:50 Poz, 6% gel, 2 lbs. Tuf-Plug per sx.

Rig released 3/15/78.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED E. E. SVOBODA TITLE Area Adm. Supvr. DATE 4/6/78

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: