

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)

Form approved.  
Budget Bureau No. 42 R1424.  
5. LEASE DESIGNATION AND SERIAL NO.

NM 013688

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR  
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR  
P. O. Box 990, Farmington, New Mexico 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface  
1825' N, 1100' W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)  
6297' GL

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Atlantic Com B

9. WELL NO.  
8A

10. FIELD AND POOL, OR WILDCAT  
Blanco Mesa Verde

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 23, T-31-N, R-10-W  
NMPM

12. COUNTY OR PARISH  
San Juan

13. STATE  
New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

12-09-76 T.D. 3433'. Ran 88 joints 7", 20#, KS intermediate casing, 3419' set at 3433'. Cemented with 373 cu. ft. cement. W.O.C. 12 hours, held 1200#/30 minutes.

12-14-76 T.D. 5771'. Ran 77 joints 4 1/2", 10.5#, KS casing liner, 2487' set 3284-5771'. Float collar set at 5754'. Cemented with 455 cu. ft. cement. WOC 18 hours.

12-17-76 P.B.T.D. 5754'. Tested casing to 4000#, ok. Perfed C.H. and Menefee 4609, 4732, 4751, 4839, 4843, 4847, 4851, 4855, 4858, 4890, 4919, 4925, 4931, 4937, 4967, 4971, 4974, 5044, 5048, 5074, 5077 with 1 shot per zone.

Faced with 47,000#--20/40 sand and 47,000 gallons water. No ball sets dropped. Flushed with 6885 gallons water.

Perfed P.L. 5330, 5332, 5334, 5346, 5349, 5367, 5370, 5374, 5378, 5381, 5420, 5243, 5465, 5470, 5506, 5510, 5544, 5578, 5583, 5634, 5637 with 1 shot per zone. Faced with 44,000#--20/40 sand and 39,000 gallons water. No ball sets dropped. Flushed with 7308 gallons water.

18. I hereby certify that the foregoing is true and correct

SIGNED

*D. G. Dices*

TITLE

Drilling Clerk

DATE

January 3, 1977

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

