

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF-077648

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Davis

9. WELL NO.

#3-A

10. FIELD AND POOL, OR WILDCAT

Blanco Mesa Verde

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 1, T31N, R12W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

1. OIL
WELL ☐ GAS
WELL ☒ OTHER

2. NAME OF OPERATOR

Aztec Oil & Gas Company

3. ADDRESS OF OPERATOR

P. O. Drawer 570, Farmington, New Mexico 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

790' FSL & 790' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6324' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

FULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐


Casing Report ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

2-17-77 Ran 76 joints of 7", 20#, K-55, 8rd casing. Total 3148.99', shoe set at 3160', insert float valve set at 3119'. Cemented with 100 sacks of 65/35 Poz Class "B" with 12% gel and 70 sacks of Class "B" with 2% CaCl. Plug down at 10:50 AM.

2-20-77 Ran 63 joints of 4-1/2", 10.50#, C-55, 8rd casing. Total 2496.61', shoe set at 5542', float collar at 5541', TIW liner hanger at 3036'. Cemented with 20 barrels gel water, 245 sacks Class "B" cement with 4% gel, 1/4 cu. ft. fine gilsonite per sack and .6% of D-19. Plug down at 5 PM.



18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

District Production Manager

DATE

February 21, 1977

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: