16.

UNITED STATES DEPARTMENT OF THE INTERIOR verse side

SUBMITE IN TRACE TO SELECT

Budget Bureau LEAST DESIGNATION

TE INDIAS, ALMOTTER OR TRIBE NAME

013688

FAPHINGTON.

GEOLOGICAL SURVEY

CLUMBBY	LICTICEC	ALID	DEDCODEC	\sim 1	11/51/6	
ZHMDRY.	NUMBER	AND	REPORTS	()	WHII	١.

tDo not use this form for pro Use "APPL		
OIL GAS X OTHER		7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR		S. FARM OR LEASE NAME
EL PASO NATURAL 3. ADDRESS OF OPERATOR	, GAS COMPANY	Atlantic 9. Well No.
	GTON, NEW MEXICO 87401 on clearly and in accordance with any State requirements.	6A (PM) 10. FEED AND POOL, OR WILDCAT
900'N, 1800'W		Blanco, PC, G, Blanco, MV 11. sec., T., R., M., OR BLK, AND SURVEY OR AREA
		Sec. 22, T-31-N, R-10-W
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)	N.M.P.M. 12. COUNTY OR PARISH 13. STATE
	6256' GL	San Juan New Mexico

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOT	CICE OF	INTENTION TO:	SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF		PULL OR ALTER CASING MULTIPLE COMPLETE	1	AIRING WELL,
SHOOT OR ACIDIZE		ABANDON*	 SHOOTING OR ACIDIZING ABAY	NDONMENT*
REPAIR WELL (Other)		CHANGE PLANS	 (Other) (Note: Report results of multiple com Camplelion or Recompletion Report and	pletion on Well

- 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*
 - T.D. 3511'. Ran 83 joints 7", 20#, K-55 intermediate casing, 3398' set at 7/8/77 3410'. Cemented with 508 cu. ft. cement. W.O.C. 12 hours, held 1200#/30 minutes. Top of cement at 2600'.
 - T.D. 5641'. Ran 59 joints 4 1/2", 10.5#, K-55 casing liner, 2449' set 3192-7/12/77 5641'. Float collar set at 5624'. Cemented with 365 cu. ft. cement. WOC. 18 hours.
 - 10/3/77 PBTD 5624'. Tested casing to 4000#, OK. Perfed Pictured Cliffs 5024-40, 3044-54, 3062-78, 3086-92' w/16 SPZ. Fraced with 45,000# 20/40 sand and 51,000 gallons water. Dropped 3 sets of 16 balls each. Flushed with o342 gallons water. Perfed C.H. 4521,4615,4657,4741,4749,4757,4765,4773,4793,4798, 4803,4815,4821,4827,4833,4864,4873,4967 w/1 SPZ. Fraced with 61,000# 20/40 sand and 115,940 gallons water. Flushed with 6350 gal. water. Perfed P.L. 5038, 5058, 5095, 5103, 5163, 5232, 5256, 5291, 5294, 5297, 5300, 5303, 5347, 5350, 5353, 5356,5359,5394,5421,5435,5487,5529,5567,5594! w/l SPZ. Fraced with 80,000# 20/40 sand and 154,000 gallons water. Flushed with 6680 gal. water.

18. I hereby certify that the foregoing is true and correct	TITLE	Drilling	Clex DATE 10/3/77
(This space for Federal or State office use) APPROVED BY	TITLE		RECEIVED
CONDITIONS OF APPROVAL, IF ANY:			OCT 14 19// OIL CON. COM. OCT 1 3 1977 DIST. 3
*Se	e Instructio	ns on Reverse S	Side DIST. 3