Form 9 334 (May 1963)

16.

UNITED STATES DEPARTMENT OF THE INTERIOR (Other instructions on reverse side)

SUBMIT IN TRIPLACATES

Form approved. Budget Bureau No.	BE RIE
LEASE DESIGNATION AND S	

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SF 078039

GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS C	N	WELLS
------------------------------	---	-------

(Do not use this form for propos Use "APPLICA	als to drill or to deepen or plug back to a different reservoir, .TION FOR PERMIT—" for such proposals.)		
OIL GAS WELL X OTHER		7. UNIT AGREEMENT N	AME
2. NAME OF OPERATOR El Paso Natural Gas Co	mnany	8. FARM OR LEASE NA	ME
3. Address of Operator P. O. Box 990, Farming		Barnes 9. WELL NO.	
4. Location of Well (Report location c See also space 17 below.) At surface 1050 ' N, 1000 '	2A (PM) 10. FIELD AND FOOL, OR WILDCAT Blanco P.C. Ext. Blanco Mesa Verde 11. SEC., T., R., M., OR BLE, AND		
,		Survey or Area Sec. 22, T-3 NMPM	•
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6495	12. COUNTY OF PARISH	13. STATE

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:			SUBSEQUENT REPORT OF:		
TEST WATER SHUT-OFF		PULL OR ALTER CASING		WATER SHUT-OFF X	REPAIRING WELL
FRACTURE TREAT		MULTIPLE COMPLETE		FRACTURE TREATMENT	ALTERING CASING
SHOOT OR ACIDIZE		ABANDON*		SHOOTING OR ACIDIZING	ABANDONMENT*
REPAIR WELL		CHANGE PLANS		(Other)Squeeze liner	l v
(Other)				(Note: Report results of multiple Completion or Recompletion Repo	e completion on Well

17. DESCRIBE PROPOSED OF COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

- T.D. 3580'. Ran 86 joints 7", 20#, K-55 intermediate casing, 3570' set at 3580'. Cemented with 468 cu. ft. cement. WOC 12 hours; held 1200#/30 minutes. 05-05-77 Top of cement at 1700'.
- Ran 76 joints 4 1/2", 10.5#, K-55 casing liner, 2433' set at Float collar set at 5842'. Cemented with 422 cu. ft. cement. 05 - 09 - 773425-5858'. WOC 18 hours.
- Ran Bond Log. No cement from 3770' to top of liner hanger at 3425'. 07-16-77 packer set at 3260', and squeezed with 150 sacks cement. WOC.
- PBTD 5842'. Tested casing to 3500#, ok. Perfed P.C. 3221, 3225, 3229, 3232, 3240, 3243, 3247, 3251 3254, with 1 SPZ. Fraced with 44,000#--10/20 sand and 45,192 gallong water. No ball sets dropped. Flushed with 5378 gallons water. Perfed C.H. Menefee 4739-44, 4841-45, 4888-92, 4906-10, 5039-43, 5053-64, 5076 200 5304 5302 5317 37 311 32 SPZ. 07-19-77 5076-90, 5194-5200, 5217-23 with 12 SPZ. Fraced with 50,000#--20/40 sand and 35,278 gallons water. Dropped 5 sets of 12 balls each. Flushed with 6762 gallons water. Perfed Upper Point Lookout 5311-17, 5344-70, 5442-53, 5488-96, 5515-25, 5557-75' with 16 SPZ. Fraced with 72,000#--20/40 sand and 41,800 gallons water. Dropped 5 sets of 16 balls each. Flushed with 6930 gallons water. Perfed Lower Point Lookout 5672-78, 5689-93, 5707-5711, 5759-65, 5776-87' with 10 SPZ. Fraced with 30,000#--20/40 sand and 30,000 gallons water. Dropped 4 sets of 10 balls each. Flushed with 7140 gallons water.

18. I hereby certify that the foregoing is true and correct SIGNED	TITLE	Drilling Clerk	DATE July 26, 1977
(This space for Federal or State office use) APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	TITLE	AUG 2 1977	DATJUL 2 8 1977
*Se	e Instructions	AUG 2 1977 OIL CON. COM. s on Reverse SPINST. 3	U. S. GEOLOGICAL SURVEY