UNITED STATES DEPARTMENT OF THE INTERIOR (Other Instructions on reverse side)

F/rm approved,
lyudget Bureau No. 42 R1421.
5. LEANE DESIGNATION AND SERIAL NO.
SF078039

		51:078059			
SUNDRY NOTICES AND REPORTS ON WELLS. (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)				6. IF INDIAN, ALLOTTEE OR THIBE NAME	
I. OIL GA				7. UNIT AGREEMENT NAME	
WELL WELL OTHER 2. NAME OF OPERATOR				8. FARM OR LEASE NAME	
El Paso Natural Gas Company				Barnes	
3. ADDRESS OF OPERATOR				9. WELL NO.	
P. O. Box 990, Farmington, NM 87401				6A (PM)	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1.720 * S, 850 * E				10. FIELD AND POOL, OR WILDCAT Blanco Pictured Cliffs Blanco Mesa Verde 11. SHC., T., R., M., OR BLK. AND SURVEY OR ARBA	
1.720 3, 0	30 L	Sec. 23, T-32-N, R-11-			
				N.M.P.M.	
14. PERMIT NO.		15. ELEVATIONS (Show wheth	er DF, RT, GR, etc.)	12. COUNTY OR PARISH 13. STATE	
		6451' GL		San Juan N.M.	
16.	Check A	ppropriate Box To Indica	te Nature of Notice, Report, c	or Other Data	
	NOTICE OF INTE	NTION TO:	SUB	SEQUENT REPORT OF:	
TEST WATER SI	IUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	X REPAIRING WELL	
FRACTURE TREA	т	MULTIPLE COMPLETE	FRACTURE TREATMENT	X ALTERING CASING	
SHOOT OR ACIDI	ZE	ABANDON*	SHOOTING OR ACIDIZING	ABANDONMENT*	
REPAIR WELL		CHANGE PLANS	(Other)(Note: Report res	sults of multiple completion on Well	
(Other) 17. DESCRIBE PROPOS	ED OR COMPLETED OF	ERATIONS (Clearly state all per	Completion or Reco	ompletion Report and Log form.) ates, including estimated date of starting an ortical depths for all markers and zones pert	
nent w this w	ork.) ·				
	3566'. Cemminutes. T	ented with 466 cu. Op of cement at 25	ft. cement. WOC 12		
05-19-77	T.D. 5952'. Ran 79 joints 4 1/2", 10.5#, K-55 casing liner, 2556' set 3396-5952'. Float collar set at 5935'. Cemented with 445 cu. ft. cement. WOC 18 hours.				
08-02-77	3232-44' wi gallons wat water. Per 5048', 5050 5191', 5376 and 50,900 5464', 5467 5557', 5559 5896' with	th 1 shot per zone cer. Dropped 1 set fed M.V. 4728', 47 1', 5053', 5067', 5 1', 5433' with 1 sh gallons water. F1 1', 5470', 5473', 5 1', 5626', 5686', 5 1 shot per zone.	t of 12 balls. Flusher 732', 4735', 4879', 48 5069', 5090', 5095', 5 not per zone. Fraced lushed with 7400 gallo 5476', 5501', 5504', 5 5703', 5706', 5746', 5	0#20/40 sand and 57,700 ed with 5540 gallons 382', 5029', 5032', 5035', 5100', 5103', 5105', 5189', with 50,000#20/40 sand	
18. I hereby certify SIGNED	that the foregoing by the foregoing by the foregoing from the foregoing the foregoing that the foregoing the foreg	CO TITLE	Drilling Clerk	DATE August 5, 19	
				' KLCEWED	
APPROVED BY CONDITIONS O	F APPROVAL, IF	ANY:	A11	DATE TO A DATE	

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY