

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 010989

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT--" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR EL PASO NATURAL GAS COMPANY		8. FARM OR LEASE NAME Fields	
3. ADDRESS OF OPERATOR Box 990, Farmington, New Mexico 87401		9. WELL NO. 1 A	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 980'N, 1460'W		10. FIELD AND POOL, OR WILDCAT Blanco Mesa Verde	
14. PERMIT NO.		12. COUNTY OR PARISH San Juan	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6268/ GL		13. STATE N.M.	
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 25, T-32-N, R-11-W N.M.P.M.			

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

6-18-77 T.D. 3475'. Ran 85 joints 7", 20#, K-55 intermediate casing, 3462' set at 3475'. Cemented with 446 cu.ft. cement. W.O.C. 12 hr.held 1200#/30 mins. Top of cement at 2200'.

6-20-77 T.D. 5696'. Ran 73 Jts. 4 1/2", 10.5#, K-55 cas. liner, 2380', set 3316-5696'. Float collar set at 5677'. Cemented with 421 cu.ft. cement. WOC. 18 hrs.

08-07-77 Ran Bond log. Perfed casing at 5313-15' and squeezed W/75 SKS cement. Well
thru on vacuum. W.O.C. cemented W/75 SKS cement . W.O.C. Perfed 4990-92' and
08-10-77 squeezed W/75 SKS Cement. Well on vacuum. W.O.C. cemented W/75 SKS cement.
W.O.C. Perfed 4569-70; Squeezed W/50 SKS cement. W.O.C. Ran cement bond
log and re-squeezed perfs at 5313-15' W/50 SKS. Cement. W.O.C.

08-11-77 P.B.T.D. 5677'. Tested casing to 3500#, O.K. Perfed C.H. 4569-83,4672-81,
4717-26,4814-24,4873-81,4891-99,4911-42' W/18 SPZ. Fraced with 71,000# 20/40
Sand and 54,600 gallons water. Dropped 4 sets of 18, 2 sets of 8 balls each.
Flushed with 6900 gallons water. Perfed Men. 4990-5006,5015-24,5042-50,5218-2'
5248-54' W/16 SPZ . Fraced with 45,000# 20/40 sand and 45,000 gallons water.
Dropped 3 sets of 16, 1 of 8 balls each. Flushed with 2950 gal waters.
Perfed upper PL 5313-28,5340-50,5372-89,5399-5415,5432-40,5457-61,5471-75'
W/16 SPZ. Fraced with 71,000# 20/40 sand and 51,500 gallons water. Dropped
6 sets of 16 balls each. Flushed with 7200 gal water. Perf. Lower P.L.
5529-33,5548-54,5585-90,5600-05,5622-28,5646-52' W/12 SPZ. Fraced W/36,000#
20/40 sand and 36,700 gallons water. Dropped 2 sets of 12 balls each. (over

18. I hereby certify that the foregoing is true and correct

SIGNED M. G. DriscoTITLE ClerkDATE Aug. 25, 1977

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE AUG 25 1977

U. S. GEOLOGICAL SURVEY

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO 680-160

Flushed w/7200 gallons water.

Flushed w/7200 gallons water.