

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

OCT 25 1990

OIL CON. DIV.
DIST. 3

FORM APPROVED
Budget Bureau No. 1004-1135
Expires September 30, 1990

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well <input type="checkbox"/> Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other	5. Lease Designation and Serial No. NM-010989
2. Name of Operator Amoco Production Company Attn: John Hampton	6. If Indian, Allottee or Tribe Name
3. Address and Telephone No. P.O. Box 800, Denver, Colorado 80201	7. If Unit or CA, Agreement Designation
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 1500' FSL x 850' FEL, Sec. 25-32N-11W	8. Well Name and No. Fields LS 2A
	9. API Well No. 30-045-22399
	10. Field and Pool, or Exploratory Area Blanco Mesaverde
	11. County or Parish, State San Juan, New Mexico

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION
<input type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Plugging Back
	<input type="checkbox"/> Casing Repair
	<input type="checkbox"/> Altering Casing
	<input type="checkbox"/> Other
	<input type="checkbox"/> Change of Plans
	<input type="checkbox"/> New Construction
	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Water Shut-Off
	<input type="checkbox"/> Conversion to Injection
	Cathodic protection well

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Amoco Production Company plugged and abandoned the cathodic protection well associated with the above well as follows:

1. Cleaned out hole with foam to 140'. Hole sluffing in.
2. Set 20' of 60 plastic csg & jetted out to 340' with foam. Hole sluffing in.
3. Jetted in hole to 320' with foam. Hole sluffing in.
4. Washed out to 350' with mud. Unable to make hole.
5. TIH with 5 7/8 bit to 280'. Torqued up 50H to 80', hung up on cables. Worked pipe & back reamed to surf.
6. With 6 1/8 concave junk mill, milled to 485'. Got shale back. TOH.
7. Pmp 80 sx class G cmt. Mixer broke down.
8. Tagged cmt top @ 168'. Pmp 100 sx class G cmt to surf.
9. Install marker.

ACCEPTED FOR RECORD
FARMINGTON RESOURCE AREA

OCT 16 1990

14. I hereby certify that the foregoing is true and correct

Signed <u>J. Hampton</u>	Title <u>Sr. Staff</u>	Date <u>9/26/90</u>
(This space for Federal or State office use)		

Approved by _____ Title _____ Date _____
Conditions of approval, if any:

NMOCD

RECEIVED

NOV 12 1991

Form 3160-5
(June 1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
Durango, Colorado

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Amoco Production Company

Attn: J.L. Hampton

3. Address and Telephone No.

P.O. Box 800 Denver, CO 80201

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1500' FSL, 850' FEL, Sec. 25, T32N-R11W

5. Lease Designation and Serial No.
NM-010989

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Fields LS 2A

9. API Well No.

30-045-22399

10. Field and Pool, or Exploratory Area

Blanco Mesaverde

11. County or Parish, State

San Juan, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Cathodic Protection
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Amoco requests permission to drill a ground bed cathodic protection well at the above location to service the producing well.

Please see the attached procedures.

RECEIVED

NOV 25 1991

OIL CON. DIV. J
DIST. 3

ACCEPTED FOR RECORD
FARMINGTON RESOURCE AREA

NOV 20 1991

FARMINGTON, NEW MEXICO
BY *[Signature]*

Please contact Cindy Burton (303)830-5119 if you have any questions.

14. I hereby certify that the foregoing is true and correct

Signed

[Signature]

Title

SR Staff Admin Supv.

Date

11/11/91

Approved by

Conditions of approval, if any:

Title

NMOCH

Date

ations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special in-

structions concerning the use of this form and the number of copies to be submitted, particularly with regard to local area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

SPECIFIC INSTRUCTIONS

Item 4—If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 13—Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive

zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

NOTICE

The Privacy Act of 1974 and the regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et. seq., 351 et. seq., 25 U.S.C. et. seq.; 43 CFR 3160.

PRINCIPAL PURPOSE — The information is to be used to evaluate, when appropriate, approve applications, and report completion of secondary well operations, on a Federal or Indian lease.

ROUTINE USES:

- (1) Evaluate the equipment and procedures used during the proposed or completed subsequent well operations.
- (2) Request and grant approval to perform those actions covered by 43 CFR 3162.3-2(2).
- (3) Analyze future applications to drill or modify operations in light of data obtained and methods used.
- (4)(5) Information from the record and/or the record will be transferred to appropriate Federal, State, local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecutions.

EFFECT OF NOT PROVIDING INFORMATION — Filing of this notice and report and disclosure of the information is mandatory once an oil or gas well is drilled.

The Paperwork Reduction Act of 1980 (44 U.S.C. 3501, et. seq.) requires us to inform you that:

This information is being collected in order to evaluate proposed and/or completed subsequent well operations on Federal or Indian oil and gas leases.

This information will be used to report subsequent operations once work is completed and when requested, to obtain approval for subsequent operations not previously authorized.

Response to this request is mandatory for the specific types of activities specified in 43 CFR Part 3160.

BURDEN HOURS STATEMENT

Public reporting burden for this form is estimated to average 25 minutes per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management, (Alternate) Bureau Clearance Officer, (WO-771), 18 and C Streets, N.W., Washington, D.C. 20240, and the Office of Management and Budget, Paperwork Reduction Project (1004-0135), Washington, D.C. 20503.

Attachment 2: Deep Groundbed Installation

Construction Practices for the installation of deep groundbeds will include, but are not limited to the following:

1. MIRSU. Trench out pit for drill cuttings and drilling fluid. Holes should be drilled with air, if possible. If it becomes necessary to drill with mud, water used to drill must be readily identified as potable.

2. Drill a 6 3/4 inch hole to a depth of 320 feet. Monitor and document drill cuttings to characterize subsurface strata from surface to TD.

3. If hole will stand open, no casing shall be used. If hole will not stand open, 100 feet of 6" PVC casing shall be installed and cemented behind pipe for the total length of the casing. This will be an adder where necessary; please include cost as a separate item.

4. Load hole with water if it was not required for drilling. If water was used for drilling, circulate the hole bottoms up to clean out the drill cuttings and to displace drilling muds with fresh water. All water used must meet the requirements outlined in step #1.

5. Log the hole with an anode utilizing a portable power supply with a minimum voltage of 12V DC at 5 foot intervals beginning at 50 feet to TD, recording both voltage and amperage at each point.

6. From the log, choose 12 anode locations meeting the following criteria:

- a. Minimum anode spacing 10 feet center to center.
- b. Balanced current distribution along anode string.
- c. Insure top anode is below water table.

Please include cost of further drilling if required to meet the above criteria.

7. Anodes will be 2" x 60" high silicon cast iron. Lower PVC vent pipe (bottom plugged) to TD. Vent pipe will be slotted below the water table, with no perforations at or above the water table. Lower each anode to its desired depth. Carefully inspect each anode cable for defects; care should be taken to insure that the anode and its cable does not become damaged during installation. Confirm the exact location of each anode to its desired depth by matching its current output to the amperage taken during the logging operation.

8. Rig up coke breeze pumping unit and carefully lower discharge hose to the bottom of the hole. With hose in place, begin pumping slurried backfill while monitoring bottom anode's current output. When backfill reaches the bottom anode, slowly retract the discharge hose at a rate roughly equal to the rate that the

backfill is rising in the hole. Move the applied power to the next anode and continue this process until the backfill is 50 feet above the top aquifer, or to surface, whichever is lower. If 50 feet above the top aquifer leaves the hole open, fill the remaining hole with metallurgical coke breeze/30% portland cement mix by volume.

9. Wire the anodes and power supply leads into the junction box. Each junction box will be equipped with numbered 0.01 ohm shunts, and provisions to allow for connection of groundbed supply leads from old or future parallel groundbeds. Securely attach the junction box to a 4" x 4" treated hardwood post in close proximity to the groundbed with the top of the junction box 24" above grade. Conduit should be provided for the entrance of anode and power supply leads into the junction box from below grade.

10. Within 10 days of completing each groundbed (deep or conventional), provide as-built drawings showing exact cable and anode locations and depths, resistance logs, groundbed anode placement, subsurface strata findings, as well as initial operational data of the cathodic protection system.

11. Backfill all trenches, pits and augured holes to grade and remove all debris generated during the installation.