

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
2. NAME OF OPERATOR
El Paso Natural Gas Company
3. ADDRESS OF OPERATOR
P. O. Box 990, Farmington, New Mexico
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 850' S, 1850' E
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF ☐ ☒
FRACTURE TREAT ☐ ☒
SHOOT OR ACIDIZE ☐ ☐
REPAIR WELL ☐ ☐
PULL OR ALTER CASING ☐ ☐
MULTIPLE COMPLETE ☐ ☐
CHANGE ZONES ☐ ☐
ABANDON* ☐ ☐
(other) ☐ ☐

5. LEASE
NM 013685
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Schwerdtfeger
9. WELL NO.
1A
10. FIELD OR WILDCAT NAME
Blanco Mesa Verde
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 27, T-31-N, R-9-W
NMPM
12. COUNTY OR PARISH
San Juan
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6160' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5-20-77 T.D. 3300'. Ran 83 joints 7", 20#, K-55 intermediate casing, 3286' set at 3300'. Cemented with 370 cu. ft. cement. WOC 12 hours; held 1200#/30 minutes. Top of cement at 1500'.

5-24-77 T.D. 5600'. Ran 76 joints 4 1/2", 10.5#, K-55 casing liner, 2460' set 3140-5600'. Float collar set at 5583'. Cemented with 430 cu. ft. cement. WOC 18 hours.

12-01-77 PBT 5583'. Tested casing to 3500#, ok. Perfed 4463-77, 4690-94, 4705-11, 4761-77, 4777-94, 4805-15' with 16 shots per zone. Fraced with 52,500#--20/40 sand and 53,000 gallons water. Dropped 5 sets of 16 balls each. Flushed with 6000 gallons water. Perfed 4846-54, 4884-96, 4912-29, 5043-50, 5061-80, 5093-5100' with 16 shots per zone. Fraced with 52,500#--20/40 sand and

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED A. G. Buice TITLE Drilling Clerk DATE December 5, 1977

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

