| Form.9-331 C (Ma; 1963) | SUBMIT IN TRIPLICATE [®] Form approved. (Other instructions on Budget Bureau No. 42-R1423 | | | | | roved. reau No. 42-R1425. | | |
|---|---|-----------------------|-------------|--|------------------|--|---------------------------------|--|
| | | ED STATES | | reverse a | | | | |
| DEPARTMENT OF THE IN | | | | RIOR | | 30 - 04 5 - 22428 5. LEASE DESIGNATION AND BEBIAL NO. | | |
| GEOLOGICAL SURVEY | | | | | <u>NM 01368</u> | | | |
| APPLICATIO | n for permit 1 | o drill, i | DEEP | en, or plug e | BACK | 6. IF INDIAN, ALLO | TTEE OR TRIBE NAME | |
| | | DEEPEN | | PLUG BA | ск 🗌 | 7. UNIT AGREEMEN | TNAME | |
| b. TIPE OF WELL OIL WELL V 2. NAME OF OPERATOR | VELL X OTHER | | | INGLE MULTIP ONE X ZONE | | S. FARM OR LEASE | NAME | |
| | atural Gas Co | mpany | | | | Atlantic 9. WELL NO. | | |
| 3. ADDRESS OF OPERATOR | | <u></u> | | | | 5A | | |
| | 0, Farmington | | | | | 10. FIELD AND POO | L, OR WILDCAT | |
| 4. LOCATION OF WELL (B At surface | leport location clearly and | | th any i | State requirements.*) | | | esa Verde | |
| | 950'S, 180 | 0.E | | | • | 11. SEC., T., B., M., AND SURVEY OF | R AREA | |
| At proposed prod. zou | ne | | | | | NMPM | Γ−31−N,R−10−W | |
| 14. DISTANCE IN MILES | AND DIRECTION FROM NEAR | EST TOWN OR POS | T OFFIC | E [‡] | | 12. COUNTY OR PAR | ISH 13. STATE | |
| | | | | | | San Juan | NM | |
| 15. DISTANCE FROM PROP LOCATION TO NEARES | Т | | 16. N | 0. OF ACRES IN LEASE | | 7. NO. OF ACRES ASSIGNED TO THIS WELL | | |
| PROPERTY OR LEASE (Also to nearest dr) | g. unit line, if any) | | | | - | 309.96 | | |
| 18. DISTANCE FROM PROD TO NEAREST WELL, I OR APPLIED FOR, ON TH | RILLING, COMPLETED, | | 19. P | ROPOSED DEPTH 5700 ' | | 20. ROTARY OR CABLE TOOLS Rotary | | |
| 21. ELEVATIONS (Show wh | | | 1 | | 1-10 041 | | WORK WILL START* | |
| 6314'GL | | | | | - | | : | |
| 23. | P | ROPOSED CASI | NG AN | D CEMENTING PROGR. | AM | | | |
| SIZE OF HOLE | SIZE OF CASING | WEIGHT PER F | | | _ | QUANTITY OF CEMENT | | |
| $\frac{13 3/4"}{2 3 (4")}$ | 9 5/8" | 32.3# | | 200' | | u.ft. to a | | |
| <u> </u> | 4 1/2" | <u>20.0#</u> 10.5# | | <u>3430'</u> 3280-5700' | | | over Ojo Alamo Eill to 3280' | |
| 0 1/4 | 1 1/2 | 10.5# | | 5200-5700 | 422 (| .u.ic. co i | .111 (0 5200 | |
| | | | | | • | • | | |
| Selective: | ly perforate | and sandw | vate | r fracture th | he Mes | aVerde for | mation. | |
| A 3000 ps: blind and | i WP and 6000 pipe rams wi | psi test ll be use | do d f | uble gate pro or blow out p | evente prever | er equipped | ł with nis well. | |
| | | | | | A Startes | | · | |
| This gas t | is dedicated. | • | | | | | • · · · | |
| j | | | | | | - Lollin L | NEL | |
| | | | | | - MAR | | al V Autom | |
| The E/2 of Section 22 is dedicated to this well. Oil Cold Cold Cold Cold Cold Cold Cold Col | | | | | | | | |
| | | | | | سان کم | DIST. MAY 4 | , 0 1011 | |
| | | | | | NAR CO. S. O. S. | | | |
| IN ABOVE SPACE DESCRIB | e proposed program : If 1 | proposal is to deep | pen or j | plug back, give data on p | resent prod | luctive zone and pro- | posed new productive | |
| sone. If proposal is to preventer program, if an | drill or deepen directiona | lly, give pertinent | t data (| on subsurface locations an | nd measure | d and true vertical d | epths. Give blowout | |
| 24. A | , 1 - | | | | <u>.</u> | · · · · · · · · · · · · · · · · · · · | | |
| SIGNED A. D | . Ausco | T 13 | PT.# | Drilling | Clerk | | cch 25, 1977 | |
| | ara) or State office use) | | | | | | | |
| (Amia space for Fede | eral or State office use) | | | | | | | |
| PERMIT NO. | | | | APPROVAL DATE | | | | |
| | | | | | | | | |
| CONDITIONS OF APPROV | AL, IF ANY : | TI1 | rl e | ······································ | - | DATE | <u> </u> | |
| | | | | | | | | |
| 4 | | | | | | | | |

*See Instructions On Reverse Side

NEW MEXICO OIL CONSERVATION COMMISSION WELL LOCATION AND ACREAGE DEDICATION PLAT

•

| | | All distances mu | at be from the out | er boundaries of | the Section. | | |
|----------------------------|--|---|--------------------|----------------------|-----------------------|---|---|
| Operator EL | PASO NATURAL | GAS COMPANY | Lease ATLA | NTIC | (NM- | 013688) | well No. 5A |
| Juit Letter | Section 22 | Townsnip 31-N | Rang | ° 10-W | County | SAN JUAN | |
| Actual Footage Loc 950 | | SOUTH | . 1800 |) • | | EAST | |
| Fround Level Flev. 6314 | feet from the Producing Fo | | e and Fool | BLANCO · M | et from the | | Dedicated Acreage: 309.96 |
| | | ated to the subje | ct well by col | | | | Acres |
| | nan one lease is nd royalty). | dedicated to the | e well, outline | each and ide | entify the o | wnership th | ereof (both as to working |
| | | different ownershi unitization, force- | | l to the well, | have the in | nterests of | all owners been consoli- |
| Yes | No If a | inswer is "yes," t | ype of consoli | dation | | | ····· |
| | is "no," list the f necessary.) | owners and tract | descriptions v | which have a | ctually bee | n consolida | ted. (Use reverse side of |
| . No allowal | ble will be assign |) or until a non-st | | iminating su | ch interests | | nunitization, unitization, approved by the Commis- |
| - | 1 | X | | · · · | ××××× | | CERTIFICATION |
| | | | | #5 O | | toined her | ertify that the information con- ein is true and complete to the knowledge and belief. ginal Sign (SP) D. G. Briss) |
| · | ، ــــــــــــــــــــــــــــــــــــ | 🎗 | | | 🕅 | Name | |
| | l t | X | | 1 | X | Position Drill | ing Clerk |
| | | | | 1 8 1 | | Compony | so Natural Gas |
| • | | SECKION 2 | NM-0 | 013688 | | Date | 25, 1977 |
| · · · · · · · · | | | | | | shown on notes of a under my is true a | certify that the well location this plat was plotted from field actual surveys made by me or supervision, and that the same nd correct to the best of my and belief. |
| | 1 | Ø | Ŷ | 1 1800' | | Date Survey MAR | ed CH 10, 1977 |
| | 5 6 8 8 | ×× | 950' | 2 2 2 | | | Professional Engineer |
| | | | | XXXXXXX | $X \times X \times X$ | Certificate 1 | No. 1760 |
| 330 660 | 90 1320 1650 11 | 180 2310 2640 | 2000 1500 | 1000 | <u>800 0</u> | 1 | |

.



P. O. BOX 990 FARMINGTON, NEW MEXICO 87401 PHONE: 505-325-2841

Multi-Point Surface Use Plan Atlantic #5A

- 1. Existing Road -
- Please refer to Map No. 1 which shows the existing roads. New roads which will be required have been marked on this map. All existing and new roads will be properly maintained during the duration of this project.
- 2. Planned Access Roads Please refer to Map No. 1. The grade of the access roads will be consistent with that of the local terrain. The road surface will not exceed thirty feet (30') in width. Upon completion of the project, the access road will be adequately drained to control soil erosion. Drainage facilities may include ditches, water bars, culverts or any other measure deemed necessary by trained Company personnel to insure proper drainage. Gates and/or cattleguards will be installed if necessary.
- 3. Location of Existing Wells Please refer to Map No. 2
- 4. Location of Tank Batteries, Production Facilities, and Production Gathering and Service Lines - Please refer to Maps No. 1 and No. 2. Map No. 2 shows the existing gas gathering lines. Map No. 1 shows the existing roads and new proposed access roads. All known production facilities are shown on these two maps.
- 5. Location and Type of Water Supply Water for the proposed project will be obtained from Hart Canyon Water Well.
- 6. Source of Construction Materials No additional materials will be required to build either the access road or the proposed location.

Multi-Point Surface Use Plan

Page Two

7. Methods of Handling Waste Materials - All garbage and trash materials will be put into a burn pit shown on the attached Location Plat No. 1. When clean-up operations are begun on the proposed project, the burn pit with its refuse will be buried to a depth of at least three feet (3'). A latrine, the location of which is also shown on Plat No. 1 will be provided for human waste. If large amounts of liquids are left in the reserve pit after completion of the project, the pit will be fenced until the liquids have had adequate time to dry. The location clean-up will not take place until such time as the reserve pit can be properly covered over to prevent run-off from carrying any of these materials into the watershed. No earthen pit will be located on natural drainages; all earthen pits will be so constructed as to prevent leakage from occurring.

- 8. Ancillary Facilities No camps or airstrips will be associated with this project.
- 9. Wellsite Layout Please refer to the attached Plat No. 1.
- 10. Plans for Restoration of the Surface After completion of the proposed project, the location will be cleaned and leveled. The location will be left in such a condition that will enable reseeding operations to be carried out. Seed Mixture #2 will be used. The reseeding operation will be performed during the time period set forth by the regulatory body. The location production equipment will be painted green (Federal Standard #595-34127)
- 11. Other Information The terrain is rolling hills and sandstone ledges covered with cedar and sagebrush. Cattle graze the proposed project site.

Multi-Point Surface Use Plan

Page Three

12. Operator's Representative - W

13. Certification -

W. D. Dawson, Post Office Box 990, Farmington, New Mexico 87401

I hereby certify that I, or persons under my direct supervision, have inspected the proposed drillsite and access route; that I am familiar with the conditions which presently exist; that the statements made in this plan are, to the best of my knowledge, true and correct; and, that the work associated with the operations proposed herein will be performed by El Paso Natural Gas Company and its contractors and sub-contractors in conformity with this plan and the terms and conditions under which it is approved.

March 25, 1977

D. R. Read Division Drilling Engineer

DRR:pb

I. Location: 950'S, 1800'E, Section 22, T-31-N, R-10-W, San Juan County, NM

Field: Blanco Mesa Verde

Elevation: 6324'

- II. <u>Geology:</u>
 - A. Formation Tops: Surface Nacimiento Lewis 3230' Ojo Alamo 1170' Mesa Verde 4800' Kirtland 1315' Menefee 4865' Fruitland 2665' Point Lookout 5300' Pic.Cliffs 3065' Total Depth 5700'
 - B. Logging Program: IES GR Density at 3430'. GR-Ind. and GR-Density at Total Depth.

C. Coring Program: none

- D. Natural Gauges: 4790', 4855', 5290'and at Total Depth. Also gauge any noticeable increase in gas. Record all gauges in daily drilling report and on morning report.
- III. Drilling:
 - A. Mud Program: mud from surface to 3430'. Gas from intermediate casing to Total Depth.
- IV. Materials:

4

| A. Casing Program: | Hole Size | Depth | Casing Size | Wt.&Grade |
|--------------------|-----------|------------|-------------|--------------------|
| | 13 3/4" | 200' | 9 5/8" | 32.3# H-40 |
| | 8 3/4" | 3430' | 7" | 20.0 # K-55 |
| | 6 1/4" | 3280-5700' | 4 1/2" | 10.5 # K-55 |

B. Float Equipment: 9 5/8" surface casing - Larkin guide shoe (fig. 102)

7" intermediate casing - Dowell guide shoe (fig. 50101) and Dowell self-fill insert float valve (fig. 53003), 5 B&W stabilizers (Prod. No. 637085) every other joint above shoe. Run float two joints above shoe.

4 l/2" liner - T.I.W. liner hanger with neoprene packoff. Larkin geyser shoe (fig. 222) and Larkin flapper type float collar (fig. 404 M&F).

- C. Tubing: 5700' of 2 3/8", 4.7#, J-55 8rd EUE tubing with a common pump seating nipple above perforated pup joint with bull plugged full joint for mud anchor on bottom.
- D. Wellhead Equipment: 10" 900 x 9 5/8" casing head. 10" 900 x 6" 900 xmas tree.

V. Cementing:

9 5/8" surface casing - use 190 sks. of Class "B" cement with 1/4# gel-flake per sack and 3% calcium chloride (224 cu.ft. of slurry, 100% excess to circulate to surface). WOC 12 hours. Test casing to 600#/30 minutes.

7" intermediate casing - use 149 sks. of 65/35 Class "B" Poz with 12% gel (15.52 gallons of water per sack) followed by 100 sks. of Class "B" with 2% calcium chloride (509 cu.ft. of slurry, 50% excess to cover Ojo Alamo). Run temperature survey at 8 hours. WOC 12 hours. Test casing to 1200#/30 minutes.

4 1/2" liner - precede cement with 20 barrels of gel water (2 sks. gel) Cement with 234 sks. of Class "B" cement with 4% gel, 1/4 cu.ft. of fine gilsonite per sack and 0.6% Halad-9 (422 cu.ft. of slurry, 70% excess to circulate liner).

250 El Paso Nalural Cas Company Typical Location Plat for Ness Verde and Watada Wells From wellhood to 2 From wellkes 10 ft File 12 pt cut 300' 2 1 2 2 جر 15' Truiler Keuse Energy [] Draw Works Mud Tark Jurit L ليـــــ Reserve \bigcirc 30 d'me of Water Fack Furl Tunk Latine dura Lig Z'XS'



10" 900 x 9 5/8" casing head 10" 900 x 6" 900 xmas tree

EL PASO NATURAL GAS COMPANY ATLANTIC #5A SE 22-31-10



MAP #1 .

LEGEND OF RIGHT-OF-WAYS

| EXISTING | ROADS | | | |
|----------|----------------|---------------------|-----|-----|
| EXISTING | PIPELINES | -+- | + | -+- |
| EXISTING | ROAD > PIFELIN | 03 - + - | | -+- |
| PROPOSED | ROADS | | | |
| FROPOSED | PITELHES | + | -1- | -+- |
| TROPOSED | ROAD - FIFELIE | 1E - | -+- | |

'N

Т

7

Т 30 N

EL PASO NATURAL GAS COMPANY ATLANTIC #5A SE 22-31-10



MAP #2

Proposed Lœ ation