

NO. OF COPIES RECEIVED	5
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	3

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator Aztec Oil & Gas Company		8. Farm or Lease Name Maddox Waller
3. Address of Operator P. O. Drawer 570, Farmington, New Mexico		9. Well No. 1A
4. Location of Well UNIT LETTER <u>C</u> , <u>800</u> FEET FROM THE <u>North</u> LINE AND <u>1465</u> FEET FROM THE <u>West</u> LINE, SECTION <u>14</u> TOWNSHIP <u>32N</u> RANGE <u>11W</u> NMPM.		10. Field and Pool, or Wildcat Blanco Mesaverde Blanco Pictured Cliff
15. Elevation (Show whether DF, RT, GR, etc.) 6387' GR		12. County San Juan

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐
OTHER Casing report ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7-29-77 Ran 83 jts of 7", 20#, K-55, 8rd casing. Total 3405.59', set at 3407', float set at 3363.11'. Cemented with 165 sacks 65/35 Poz A, Class B with 12% gel and 6.25# fine gilsonite per sack and 70 sacks Class B with 2% CaCl and 6.25# fine gilsinite per sack. Plug down at 3:20 PM.

8-2-77 Ran 77 jts of 4-1/2", 10.50#, 8rd, K-55 casing. Total 2490.38'. Set from 3245' to 5746', float collar set at 5745'. Cemented with 312 sacks 50/50 Poz A, Class B with 2% gel, 6.25# fine gilsonite per sack, 1/4# gel flake per sack and .6% Halad 9. Plug down at 1:00 PM.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED A. R. Kendrick

TITLE District Production Mgr. DATE August 3, 1977

Original Signed by A. R. Kendrick

SUPERVISOR 1-1-1-1-1

APPROVED BY _____

TITLE _____

DATE 10/1/77

CONDITIONS OF APPROVAL, IF ANY: