

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved
Budget Bureau No. 42 R1474

5. TASK DESIGNATION AND SERIAL NO.

SF 078316-E

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

WALKER

9. WELL NO.

1A

10. FIELD AND POOL, OR WILDCAT

Blanco Mesa Verde

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 31, T-31-N, R-9-W

N.M.P.M.

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

EL PASO NATURAL GAS CO.

3. ADDRESS OF OPERATOR

BOX 990, FARMINGTON, NEW MEXICO 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

1800'S, 850'E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6420' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☒
☒
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

☐
☐
☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

07/29/77 T.D. 3595'. Ran 87 joints 7", 20#, K-55 intermediate casing, 3582' set at 3595'. Cemented with 390 cu. ft. cement. W.O.C. 12 hours, held 1200#/30 minutes. Top of cement at 2300'.

08/01/77 T.D. 5844'. Ran 60 joints 4 1/2", 10.5#, K-55 casing liner, 2412' set 3432-5844'. Float collar set at 5827'. Cemented with 420 cu.ft. cement. WOC. 18 hours.

10/09/77 P.B.T.D. 5827'. Tested casing to 3500#, OK. Perfed C.H.-Men. 4718, 4850, 4890, 4941, 4947, 4953, 4959, 4965, 4971, 4977, 5002, 5006, 5010, 5214, 5265, 5272, 5277, 5301, 5312, 5328, 5338 w/1 SPZ. Fraced with 72,000# 20/40 sand and 72,000 gallons water. Flushed with 6680 gallons water. Perfed P.L. 5426, 5430, 5433, 5452, 5456, 5460, 5464, 5468, 5472, 5476, 5480, 5518, 5522, 5526, 5528, 5603, 5663, 5687, 5705, 5737, 5807, 5815' w/1 SPZ. Fraced with 60,000# 20/40 sand and 60,000 gallons water. Flushed with 6760 gal. water.

18. I hereby certify that the foregoing is true and correct

SIGNED

J. H. Blanco

TITLE

Drilling Clerk

DATE

10/10/77

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

OCT 14 1977

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY
FARMINGTON, N.M.