Form 9-331 (N 15 1963)	UNITED STATES DEPARTMENT OF THE IN	SUBMIT IN TRIPLICATE* (Other instructions on re-	Form approved. Budget Burea: No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO.
	GEOLOGICAL SURVI		SF-078215
(Do not u	SUNDRY NOTICES AND REPORTS to this form for proposals to drill or to deepen or Use "APPLICATION FOR PERMIT—" for	TS ON WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
	GAS	7. UNIT AGREEMENT NAME	
WE'L	WELL XX OTHER	S. FARM OR LEASE NAME	
Aztec Oil & Gas Company			Vanderslice
3. ADDRESS OF OPERATOR			9. WELL NO.
	Drawer 570, Farmington, New Me	#1-A	
See also space	VELL (Report location clearly and in accordance wie 17 below.)	10. FIELD AND POOL, OR WILDCAT	
At surface	0001 EGT & 10001 EUX	Blanco Mesa Verde	
800' FSL & 1820' FWL			11. SEC., T., R., M., OR BEK. AND SURVEY OR ABEA
			Continu 10 M201 Blow
14. PERMIT NO.	15. ELEVATIONS (Show who	ther DF, RT, GR, etc.)	Section 19, T32N, R10W 12. COUNTY OR PARISH 13. STATE
	610	52' GR	San Juan New Mexico
16.	Check Appropriate Box To India	ate Nature of Notice, Report, or C	
			ENT REPORT OF:
TEST WATER	SHUT-OFF PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL
FRACTURE TR		FRACTURE TREATMENT	ALTERING CASING
SHOOT OR AC		SHOOTING OR ACIDIZING	ABANDONMENT*
REPAIR WELL CHANGE PLANS (Other)		(Other) Cas	ing Report X
(Other)	(Other) (Note: Report results Completion or Recomp		of multiple completion on Weil etion Report and Log form.)
17. DESCRIBE PROP proposed w nent to this	OSED OR COMPLETED OPERATIONS (Clearly state all pork. If well is directionally drilled, give subsurfactionally)	ertinent details, and give pertinent dates, e locations and measured and true vertica	including estimated date of starting any I depths for all markers and zones perti-
5-22-7	Ran 81 jts of 7", 20#, K-55, ST&C casing. Total 3227', set at 3238' KB. Cemented with 170 sacks of 65/35 Class "B" Poz with 12% gel and 1/4 cu. ft. fine gilsonite per sack followed by 70 sacks Class "B" with 2% CaCl. Plug down at 1:15 AM.		
5-25-7	Ran 62 jts of 4-1/2", 10.50#, K-55, 8rd casing. Total 2560.22', shoe set at 5550', float collar at 5549', liner hanger at 2978'. Cemented with 320 sacks of 50/50 Poz A, Class "B" with 2% gel, 6.25# fine gilsonite per sack, 1/4# gel flake per sack and 0.6% Halad 9. Plug down at 7:35 AM, 5-26-77.		
		4	3 1 1977

TITLE District Production Manager May 25, 1977

TITLE DATE

U. S. GEOLOGICAL SURVEY

18. I hereby certify that the foregoing is true and correct

(This space for Federal or State office use)

APPROVED BY ______CONDITIONS OF APPROVAL, IF ANY:

 \le signed