C-27-3/-/O Location of Well: C273110 Page 1

OIL CONSERVATION DIVISION NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator: AMOCO PRODUCTION COMPANY Lease/Well #:ATLANTIC A LS 009A Meter #:93745 RTU: - - County:SAN JUAN

	NAME RESERVOIR OR POOL				TYPE PROD	METHOD	PROD	MEDIUM PROD	
PR OMP	ATLANTIC A LS 009A BPC 93			3745	GAS	FLOW		TBG	
WR OMP	ATLANTIC A LS 009A BMV 89			796	GAS	FLOW		TBG	
	.	PRE	E-FLOW	SHUT-IN	 Pressure da	TA			
	Hour/Date Shut-In Lengt			th of Time Shut-In		SI Press. PSI		G Stabilze	
PR OMP	06/07/85 (3/13			7-2	233		6 june 1		
WR OMP				12	221		- Cike		
	. I			FLOW TEST	DATE NO.1			— I — J — - —	
omme	nced at (ho	our,date)*		· · · · · · · · · · · · · · · · · · ·		Zone	Produ	cing (Upr(Lw	
(ho	TIME LAPSED (hour, date) SINCE			PRESSURE Upper Lower		Prod Temp			
06/ 07 /95 16		Day 1	Day 1		207	,	B	Both Zones Si	
0	6/ 08 /95 1 7	Day 2	?	228_	215		Be	oth Zones SI	
06/ 09 /95 18		Day 3	3	232	220		_ B	oth Zones SI	
06/10/95		Day 4	1	233	221		LEM	W lower	
06/11/95 20		Day 5	5	233	161		4		
	06/12/95 Day 6			234	154				
rodu il:_ as:	ction rate	BOPD b	pased MFCPI	D:Tested t	BBLs in heu (Orific N PRESSURE	e or Met	G er):ME	rav GOR _ TER	
PR	Hour, Date	e SI Leng	gth of	Time SI	SI Press.	PSIG	Stabil	ized (yes/no	
	1	- 1			1				
OMP WR	-				****				

ाति (

FLOW TEST NO. 2

Zana arodusina Almay ay Laura

THE	LAPSED TIME	, mo	4UNE	PROD. ZONE		
hour, 414	SINCE .	Upper Completion	Lawer Convertee	TEMP.	REMARKS	
· · · · · · · · · · · · · · · · · · ·				 		
	-					
•						
	 					
	1	[
		***************************************	A STATE OF THE PARTY OF THE PAR	THE CONTRACT OF THE CASE.		
	J	L	<u> </u>	1		
Production rate o	luring test				•	
0.1	200	5 1	D14 *			
Oil:	BOP	D based on	Bbls. if	Hours.	Grav GOR	
Gas:		MCF	PD: Tested thru	(Orifice or Meter):	
Remarks:						
						
I hereby centify t	hat the informati	<u>on herein c</u> ontain	ed is true and co	implete to the bes	t of my knowledge.	
	Johnny Role	insen		_ //	moce Strol.	
Approved	il Conservation I	Sivilian	19 (Operator	we Wet.	
New Medico	JUN 2 9	1995	1	By D	nelies Dal	
			•	4		
By	DEPUTY OIL & GAS	INSPECTOR		Tide	sklips Del elek Technologist -26-95	
_			,	300	-26-95	
1146				Jak		

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

1. A packer leskage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as presented by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following tecompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been distributed. Tests shall also be taken at any time that communication is supported or when requested by the Division.

Commenced at their, date) *

- 2. At least 72 hours prior to the commencement of any picker leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer lexisge test shall commence when both zones of the dual completion are shut in for pressure stabilization. Both zones shall remain shut in until the well-head pressure in each has stabilized, provided however, that they need not remain shut in more than seven days.
- 4. For Flow Ten No. 1, one hone of the dual completion shall be produced at the normal rate of production while the other zone remains shut in. Such tent shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well in being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shur-in, in accordance with Paragraph 3 above.
- Flow Text'No. 2 shall be conducted even though no lesk was indicated during Flow Text No. 1. Procedure for Flow Text No. 2 is to be the same as for Flow Text No. 1 except

- that the previously produced 2000 shall remain shut in while the 2000 which was previously shut in it produced.
- 2. Pressures for gas-zone term must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours term: immediately prior to the begunning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day term: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 14-hour oil zone tesu: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the securacy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aster District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas 2000s only) and gravity and GOR (oil 2000s only).