

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

PERMIT IN TRIPLICATE
(Other instructions on reverse side)

Form approved
Budget Bureau No. 42 R1421
3. LEASE DESIGNATION AND SERIAL NO.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT-" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR	8. FARM OR LEASE NAME
3. ADDRESS OF OPERATOR	9. WELL NO.
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface	10. FIELD AND POOL, OR WILDCAT
14. PERMIT NO.	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH
	13. STATE

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☒	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☒	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) ☐	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10/5/77 T.D. 3240'. Ran 78 joints 7", 20#, K-55 intermediate casing, 3228' set at 3240'. Cemented with 459 cu. ft. cement. W.O.C. 12 hours, held 1200#/30 minutes. Top of cement at 1725'.

10/9/77 T.D. 5535'. Ran 78 joints 4 1/2", 10.5#, K-55 casing liner, 2490' set 3045-5535'. Float collar set at 5519'. Cemented with 422 cu. ft. cement. WOC. 18 hours.

10/10/77 P.B.T.D. 5519'. Tested casing to 3500#, OK. Perfed C.H. 4501, 4531, 4553, 4611, 4614, 4622, 4626, 4634, 4637, 4649, 4654, 4658, 4674, 4735, 4737 w/1 SPZ. Fraced with 53,000# 20/40 sand and 54,550 gallons water. Flushed with 6200 gallons water. Perfed P.L. 4887, 4916, 4945, 4967, 4978, 5062, 5066, 5077, 5080, 5096, 5100, 5104, 5108, 5118, 5122, 5126, 5132, 5136, 5140, 5198, 5241, 5327, 5341, 5381' w/1 SPZ. Fraced with 64,000# 20/40 sand and 66,700 gallons water. Flushed with 6450 gal. water.

18. I hereby certify that the foregoing is true and correct

SIGNED *A. P. Davis*

TITLE Drilling Clerk

DATE 10/11/77

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

RECEIVED

DATE OCT 13 1977