STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator	BURLINGTON RESOURC	ES OIL & GAS CO	Lease	LUCEDNE		Well	
Location			Lease	LUCERNE A		No. 4A	
of Well:	Unit C Sect	10 Twp. 03 ² RESERVOIR OR POOL		010W	County SAN J		
	NAME OF	RESERVOIR OR POOL	I	YPE OF PROD. (Oil or Gas)	METHOD OF F (Flow or Art.		
Upper Completion	PICTURED CLIFFS			Gas	Flow	Lift) (Tbg. or Csg.) Tubing	
Lower Completion	MESAVERDE			Gas	Flow	Tubing	
	· ·	PRE-FLOW	SHUT-IN PRESS	SURE DATA			
Upper Completion	Hour, date shut-in 07/14/2000	Length of time shut-in 120 Hours	SI p	ress. psig	Stabiliz	zed? (Yes or No)	
Lower Completion	07/14/2000	72 Hours		207	······································		
Commence	d at (hour date)*	07/17/2000	FLOW TEST NO.		ATTENDED TO THE		
TIME	LAPSED TIME	PRESSURI	F	PROD. ZONE	(Upper or Lower)	LOWER	
(hour.date)	SINCE*		ver Completion	TEMP		REMARKS	
07/18/2000	96 Hours	193	151		Turned lower zone on		
07/19/2000	120 Hours	195	159				
					Opened upper zone up		
		<u> </u>	S AS	200		· ·-····	
	4		1 000 N				
Production rate	e during test	· ·		- 2 - 2			
	- ug			2\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \			
Oil:	BOPD based on	Bbls. in	Hours.		Grav.	GOR	
Gas:		MCFPD; Tested thru (Orifice	e or Meter):			· · · · · · · · · · · · · · · · · · ·	
		MID-TEST	SHUT-IN PRESS	URE DATA			
Upper Completion	Hour, date shut-in	Length of time shut-in	SI pi	ess. psig	Stabiliz	ted? (Yes or No)	
Lower Completion	Hour, date shut-in	Length of time shut-in	SI pi	ess. psig	Stabiliz	ed? (Yes or No)	
315001 366		(Cor	atinue on reverse s				

FLOW TEST NO. 2

Commenced at (hour, da	ate)**		Zone producing (Upper or Lower):					
TIME /	LAPSED TIME SINCE **	PRESSURE		PROD. ZONE TEMP.	REMARKS			
(hour, date)		Upper Completion	Lower Completion	n lean.				
	 		 					
		 	 					
Production rate du	uring test							
						GOR		
Gas:		MCFF	PD: Tested thru (C	Orifice or Meter):				
Remarks:								
Thereby certify the	hat the information h	nerein contained is tru	ue and complete to	o the best of my knowle	edge.			
	AHG - 9 2	າດ ດດ						
Approved			19	Operator Burlin	gion Resources			
New Mexico	Oil Conservation Di	vision		By More	llago			
By	at signed by Cha	IPLIE T. PRIMINI		Title Operations Associate				
	EPUTY OIL & GAS	INSPECTOR, DIST.	Date Tuesday, August 01, 2000					
	<u> </u>							

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4 For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- 5- Following completion of Flow Test No. 1, the well shall again be shut-in. in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).