

U. S. G. S.  
May 1963

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE  
(Other instructions on reverse side)

Field approved  
Budget Bureau No. 12 R4121

5. LEASE DESIGNATION AND SERIAL NO.

NM 0606

6. INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR El Paso Natural Gas Company		8. FARM OR LEASE NAME Atlantic A	
3. ADDRESS OF OPERATOR P. O. Box 990, Farmington, New Mexico 87401		9. WELL NO. 3A	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface  1150' N, 1500' W		10. FIELD AND POOL, OR WILDCAT Blanco Mesa Verde	
14. PERMIT NO.		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 28, T-31-N, R-10-W NMPM	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6045' GL		12. COUNTY OR PARISH San Juan	
		13. STATE New Mex.	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

08-28-77 T.D. 3128'. Ran 77 joints 7", 20#, K-55 intermediate casing, 3116' set at 3128'. Cemented with 348 cu. ft. cement. WOC 12 hours; held 1200#/50 minutes. Top of cement at 1400'.

08-31-77 T.D. 5438'. Ran 76 joints 7", 10.5#, K-55 casing liner, 2475' set at 2963-5438'. Float collar set at 5421'. Cemented with 423 cu. ft. cement. WOC 18 hours.

09-14-77 PBTD 5421'. Tested casing to 3500#, ok. Perforated C.H. Menefee 4553, 4573, 4380, 4412, 4426, 4460, 4506, 4516, 4526, 4536, 4546, 4556, 4596, 4695, 4707, 4727, 4829, 4845' with 1 shot per zone. Fraced with 70,000#--20/40 sand and 151,300 gallons water. Flushed with 7000 gallons water. Perforated Point Lookout 4954, 4959, 5004, 5008, 5012, 5016, 5020, 5024, 5039, 5043, 5069, 5073, 5077, 5106, 5130, 5158, 5178, 5188, 5223, 5235, 5297' with 1 shot per zone. Fraced with 65,000#--20/40 sand and 135,500 gallons water. Flushed with 6580 gallons water.

18. I hereby certify that the foregoing is true and correct

SIGNED


TITLE

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:



RECEIVED

SEP 20 1977

U. S. GEOLOGICAL SURVEY