

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Form approved,
Budget Bureau No. 42 R1424.
5. LEASE DESIGNATION AND SERIAL NO.

SF078039

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Barnes

9. WELL NO.

3A

10. FIELD AND POOL, OR WILDCAT

Blanco Mesa Verde

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 27, T-32-N, R-11-W,
N.M.P.M.

12. COUNTY OR PARISH

San Juan

13. STATE
New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. ☐ OIL
WELL ☐ GAS
WELL ☒ OTHER

2. NAME OF OPERATOR

El Paso Natural Gas Company

3. ADDRESS OF OPERATOR

P. O. Box 990, Farmington, NM 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

860'N, 1100'W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6524' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

6-9-77 T.D. 3640'. Ran 88 joints 7", 20#, K-55 intermediate casing, 3627' set at
3640'. Cemented with 580 cu. ft. cement. WOC 12 hours, held 1200#/30
minutes. Top of cement at 900'.

6-12-77 T.D. 5944'. Ran 76 joints 4 1/2", 10.5#, K-55 casing liner, 2464' set
3480-5944'. Float collar set at 5927'. Cemented with 430 cu. ft. cement.
WOC 18 hrs.

7-25-77 P.B.T.D. 5927'. Tested casing to 4000#, OK. Perfed C.H. and Men. 4876',
4923', 4940', 5064', 5067', 5103', 5106', 5111', 5115', 5118', 5121',
5135', 5138', 5152', 5155', 5158', 5312', 5344', 5386' with 1 shot per zone.
Fraced with 54,000--20/40 sand and 54,000 gallons water. Flushed with 7182
gallons water. Perfed P.L. 5521', 5531', 5535', 5539', 5565', 5569', 5572',
5581', 5584', 5587', 5590', 5593', 5638', 5663', 5673', 5716', 5734', 5738',
5814', 5851' with 1 shot per zone. Fraced with 60,000--20/40 sand and
60,000 gallons water. Flushed with 7476 gallons water.

18. I hereby certify that the foregoing is true and correct

SIGNED

A. J. Busco

TITLE

Drilling Clerk

DATE

August 1, 1977

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: