Form 9-331 (May 1963)	UNITED STATES SUBMIT IN TRIPLICATE  DEPARTMENT OF THE INTERIOR verse side)  GEOLOGICAL SURVEY						
	blu form for prote	TICES AND REDSAIS to drill or to decarron FOR PERMIT-	epen or plug he	ick to a different reservoir.	6. IF INDIAN, ALLOT	THE OR TRIBE NAME	
1. OIL GAS		7. UNIT AGREEMENT NAME					
WELL WEI	A	8. FARM OR LEASE 1	NAME				
EL PASO NATURAL GAS CO. 3. ADDRESS OF OPERATOR					Walker Com 9. WELL NO.		
BOX 990,	FARMINGTON,	2A	2A 10. FIELD AND POOL, OR WILDCAT				
4. LOCATION OF WELL See also space 17 At surface	below.)						
At surface 1140'S, 1640'E					Blanco Mesa Verde  11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA		
					Sec. 32, T	`-31-N, R-9-W	
14. PERMIT NO.		15. ELEVATIONS (Show whether DF, RT, GR, etc.)			12. COUNTY OR PAR		
			6298' G		San Juan	New Mexico	
16.	Check A	appropriate Box To	Indicate N	ature of Notice, Report, or			
	NOTICE OF INTI	ENTION TO:		SUBSE	QUENT REPORT OF:	<u></u>	
TEST WATER SHUT-OFF PULL OR ALTER CASING WATER SHUT-OFF					X REPAIRING WELL		
FRACTURE TREAT	j	MULTIPLE COMPLETE		FRACTURE TREATMENT SHOOTING OR ACIDIZING	X ALTERING ABANDON	<u>  </u>	
SHOOT OR ACIDIZ	E .	ABANDON* CHANGE PLANS		(Other)	ABADO		
(Other)				(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)			
17. DESCRIBE PROPOSI proposed work nent to this wo	. If well is direc	PERATIONS (Clearly stationally drilled, give st	te all pertinent ubsurface locat	t details, and give pertinent date ions and measured and true verti	s, including estimated cal depths for all mari	date of starting any cers and zones perti-	
8/6/77:	at 3473	T.D. 3473'. Ran 86 joints 7", 20#, K-55 intermediate casing, 3460' set at 3473'. Cemented with 390 cu.ft. cement. WOC 12 hours, held 1200#/30 minutes. Top of cement at 2250'.					
8/9/77:	5730'.	T.D. 5730'. Ran 63 joints 4 1/2", 10.5#, K-55 casing liner, 2416' set 331-5730'. Float collar set at 5713'. Cemented with 414 cu.ft. cement. WOC 18 hours.					
10/16/77:	4733-39 sand and with 655 5132-48 and 58,0 with 670 w/16 SP2 Dropped Perfed 1	, 4836-62, 485 d 51,000 gallo 50 gallons wat , 5159-68, 518 000 gallons water. Z. Fraced wit 3 sets of 16 Lower P.L. 544	95-99, 49 ons water ter. Per 83-99' w/ ater. Dr . Perfed th 80,000 balls ea 48-54, 54	3500#, OK. Perfed 03-09' w/ 16 SPZ. Propped 5 sets of fed Menefee 5002-07 16 SPZ. Fraced with copped 5 sets of 16 massive P.L. 5297-1# 20/40 sand and 88 ch. Flushed with 6 63-67, 5483-87, 549 th 35,000# 20/40 sand sand sand sand sand sand sand sand	Fraced with 50 f 16 balls each, 5012-21, 510 th 50,000# 20/balls each. F 5316, 5328-68, 000 gallons water 3-97, 5541-49,	0,000# 20/40 ch. Flushed 08-14, '40 sand Flushed 5402-17' vater.	

water. Dropped 4 sets of 16 balls each. Flushed w/7000 gallons water.

GEO! OCICAL Service