

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐  
2. NAME OF OPERATOR  
Northwest Pipeline Corp.  
3. ADDRESS OF OPERATOR  
P.O. Box 90, Farmington, New Mexico 87041  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1050' FSL & 1700' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:  
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  
TEST WATER SHUT-OFF ☐ ☐  
FRACTURE TREAT ☐ ☐  
SHOOT OR ACIDIZE ☐ ☐  
REPAIR WELL ☐ ☐  
PULL OR ALTER CASING ☐ ☐  
MULTIPLE COMPLETE ☐ ☐  
CHANGE ZONES ☐ ☐  
ABANDON\* ☒ ☐  
(other) ☐

5. LEASE  
SF 079013  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
7. UNIT AGREEMENT NAME  
San Juan 32-8 Unit  
8. FARM OR LEASE NAME  
San Juan 32-8 Unit  
9. WELL NO.  
#38  
10. FIELD OR WILDCAT NAME  
Undesignated Fruitland  
11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA  
Sec 29 T32N R8W  
12. COUNTY OR PARISH  
San Juan  
13. STATE  
New Mexico  
14. API NO.  
30-045-22534  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6638' GR.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

- 1) RU P&A Unit.
  - 2) Pump 30 sks Cl "B" cmt down 2-7/8" csg followed by 15 bbls wtr (Cmt top inside 2-7/8" will be @ 2600'; 196' above top Ojo Alamo).
  - 3) Cut csg @ freepoint.
  - 4) Spot 20 sks Cl "B" cmt on cut off (@ least 50' above to 50' below).
  - 5) Spot 30 sks Cl "B" cmt on 8-5/8" surface csg shoe (@ least 50' above to 50' below shoe).
  - 6) Spot 30' cmt plug at surface and install P&A marker.
  - 7) Release Rig.
- Subsurface Safety Valve: Manu. and Type \_\_\_\_\_

18. I hereby certify that the foregoing is true and correct

SIGNED Sterne Kateris TITLE Prod. Engr. DATE March 24, 1980

APPROVED

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

APR 11 1980  
James F. Sims  
JAMES F. SIMS

DISTRICT OIL & GAS SUPERVISOR \*See Instructions on Reverse Side

APR 14 1980

OIL CON. COM.

Set @ \_\_\_\_\_ Ft.

MAR 25 1980

U. S. GEOLOGICAL SURVEY  
DURANGO, COLO.