## **UNITED STATES**

DEPARTMENT OF THE INTERIOR	SF 079013
1	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
	7. UNIT AGREEMENT NAME
SUNDRY NOTICES AND REPORTS ON WELLS	San Juan 32-8 Unit
(Do not use this form for proposals to drill on the deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
	San Juan 32-8 Unit
1. oil gas well dother	
Well Well Other	9. WELL NO. ରାଜ୍ୟ ପ୍ରଥମ । ଜଣ୍ଡିଆ #38 ଜନ୍ମ ଓ ଜଣ୍ଡିଆ
2. NAME OF OPERATOR	
Northwest Pipeline Corporation	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Undesignated Fruitland
P.O. Box 90, Farmington, N.M. 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA display 3 control of the contro
below.) AT SURFACE: 1050' FSL & 1700' FEL	Sec 29 T32N R8W
AT TOP PROD. INTERVAL: Same	12. COUNTY OR PARISH 13. STATE
AT TOTAL DEPTH: Same	San Juan - New Mexico
	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	30-045-22534 7 5322
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	6638' GR 등등 등 등 등 등 등 등 등 등 등 등 등 등 등 등 등 등 등
TEST WATER SHUT-OFF	<b>학일절점 및 11급명점</b>
FRACTURE TREAT	
SHOOT OR ACIDIZE	
REPAIR WELL	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING	change on Form 9-330.)
MULTIPLE COMPLETE	2 25 2 2 2 3 3 3 3
ABANDON*	straud.  togo lo  tog
(other)	
	<u>। इ.स.च्या व विक्रीसर्व हैं।</u>
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and	
measured and true vertical depths for all markers and zones pertinen	t to this work.)*
1. RU P&A Unit.	
1. KO IWA DIII.	
2. Pumped 30 sx C1 "B" cement down 2-	7/01 3 3 7 3 8
to 2600'.	7/0 casing and displaced
3. Cut off 2-7/8" casing and spotted	35 sx C1 "B" cement at 600'.
4. Spotted 20 sx Cl "B" cement on surface casing at 140.	
그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그	
5. Cut off wellhead. Spotted 10 sx Cl "B" cement at surface and	
installed P&A marker 7-13-80.	
	Rigida af Baga
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	6 4 5 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6
- (a) (b) ·	
SIGNED TITLEST. Prod. En	gr DATEJuly 16, 1980
(This space for Federal or State office use)	
	WELL AND
APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:	DATE DATE
Alian -	夏声夏至 <b>引尼南 医</b> 腹畸
	(SGD. MAT MILEENBACH
ريني -	HOÆÆALIË, EËËË
*See Instructions on Reverse S	M. WILLE
/djb	M. WILLES MANAGER
/ W   D	