

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved by
Budget Bureau No. 42-R14245. LEASE DESIGNATION AND SERIAL NO.
NM 03189

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT--" for such proposals.)

1.

OIL ☐ GAS ☒ OTHER
WELL WELL

2. NAME OF OPERATOR

Northwest Pipeline Corporation

3. ADDRESS OF OPERATOR

P.O. Box 90 - Farmington, New Mexico 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)

At surface

1520' FSL & 1070' FWL

7. UNIT AGREEMENT NAME

Cox Canyon

8. FARM OR LEASE NAME

Cox Canyon

9. WELL NO.

26

10. FIELD AND FOOT, OR WILDCAT

Blanco Pictured Cliffs

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 9, R32N, T11W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6546' GR

12. COUNTY OR PARISH

San Juan

13. STATE

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐

PULL OR ALTER CASING

☐

FRACTURE TREAT

☐

MULTIPLE COMPLETE

☐

SHOOT OR ACIDIZE

☐

ABANDON*

☐

REPAIR WELL

☐

CHANGE PLANS

☐

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐

REPAIRING WELL

☐

FRACTURE TREATMENT

☐

ALTERING CASING

☐

SHOOTING OR ACIDIZING

☐

ABANDONMENT*

☐

(Other)

"Summary"

☒(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*6-18-77 Spud 12 1/4" surface hole. Drilled to 120' KB. Ran 8 5/8" csg. set
at 119' KB. Cemented with 85 sks. of Class "B" with 1/4# of Flocele/
sk. WO Rotary Rig.

6-21-77 to 6-24-77 Drilled 6 3/4" hole 3338'.

6-24-77 Ran I-ES and GR Density Logs. Ran 2 7/8" csg. set at 3320'. Cemented
with 160 sks. of Class "B" 65/35 poz with 12% gel and 12 1/2 lbs. of
fine Gilsonite per sack followed by 50 sks. Class "B".

6-25-77 Top of cement at 1250 by temp. survey.

RECEIVED

JUL 5 1977

U. S. GEOLOGICAL SURVEY
FARMINGTON, N.M.

18. I hereby certify that the foregoing is true and correct

SIGNED

D.H. Marchetti

TITLE

Sr. Drilling Engineer

DATE

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

DHM/ch

*See Instructions on Reverse Side