

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

1-00-0-1420-1709

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Ute Mtn. Ute

7. UNIT AGREEMENT NAME

None

8. FARM OR LEASE NAME

Ute Mtn. Ute

9. WELL NO.

5

10. FIELD AND POOL, OR WILDCAT

Straight Canyon Dakota

11. SEC., T., R., M., OR BLK. AND

SURVEY OR AREA

Sec. 14-Twp. 31N-R16W

N.M.P.M.

12. COUNTY OR PARISH

San Juan

13. STATE

N.M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL ☒ GAS ☐
WELL WELL OTHER

2. NAME OF OPERATOR

Robert C. Anderson

3. ADDRESS OF OPERATOR

The Summit Bldg. - Suite 415

8079 N. May Ave. Oklahoma City, Okla. 73112

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)

At surface

1650 feet south of the North line and
1650 feet west of the East line of Sec. 14-Twp. 31N-R16W.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

XXXX 5729 5734 KB

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

Well History

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)

The above captioned well was spudded on Dec. 8, 1977 and a 9 7/8" surface hole was rotary mud-drilled to a depth of 557' below GL. On 12-11-77 552' of 7" 20' surface casing was set 2' below GL to an approx. depth of 554' or approx. 559' below KB and cement cir. to the surface with 170 sx of Class "F" cement & CaCl. Casing was tested with pump press. and held 600 psig OK. On 12-12-77 a 6 1/2" hole was commenced with air drilling below the surface pipe and drilled to an approx. depth of 2335' from GL. Dakota sand was encountered in the air samples at 2325' GL & indicated very fine grain sd with light chloro-
thane cut & possibly light fluor. About same down to 2333 or 34 at which point the dusting stopped. Drilled on to 2335 with out returns. A blowy line sample at 2325 showed medium grain sand with light brown color, good cut & odor. No other shows were indicated above the Dakota. The well was then logged at this depth. Note: While drilling with air between 2325 & 2335 the Blow out preventer
rams were occasionally closed to test for gas; however, only a very slight indication of gas was noted briefly at the blowy line when air circulation was resumed to start drilling. All intentions were to log and plug the well at this point; however when pulling the drillpipe to log it was noted that the bottom approx. 1500' of the drillpipe was covered with heavy (high pour point) oil. The well was then logged (Induction-Gamma Log) to a depth of 2341' KB. and in view of the oil indication it was decided to mud-up and core. The hole was then cored from 2335' GL to 2365' GL measurement. 2335 to 36 showed tan fine grain sd with oil stain and the balance of the core from 2336 to 2365 indicated (Over)

18. I hereby certify that the foregoing is true and correct

SIGNED

Ashton B. Lerey, Jr.

TITLE

Agent for:

DATE Feb. 7, 1978

(This space for Federal or State office use)

Robert C. Anderson

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

FEB 9 1978

CONFIDENTIAL

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY
DENVER, COLO.

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

Continued from front page:-v.fine grain, light gray sand some with trace of ~~light~~ silt, and no staining. The 6 1/4" hole was then continued from this core depth of ~~2365~~ 2365', and drilled on to the driller's depth of 2394' GL measurement. T.D. was reached on 12-17-77. No other shows were indicated. Drilling stopped in the upper Dakota sand section. The well was logged at the core depth of 2365' GL (Driller's measurement) (2372 KB. Log measurement) and then drilled on to the T.D. of 2394' GL while conditioning the hole in preparation to running 4 1/2" casing. On 12-18-77 4 1/2" 10.5# K-55 casing was set to the ~~log~~ K.K. total depth of 2399.5' and cemented with 95 sacks of 50-50 Posmix. Location has been back graded and smoothed, pits fenced for cattle protection and well shut-in awaiting completion rig.

Log tops: Surface ---- Point Lookout

400' +??----	Mancos top (not definite)
1698'	----- Gallup sand zone (no show indicated)
1852'	----- Sanastee
2218'	----- Greenhorn
2274'	----- Graneros
2331'	----- Dakota sd.

T.D. (Logged to 2374). Drilled on to a KB of 2399.5.