

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
 2. NAME OF OPERATOR
EL PASO NATURAL GAS CO.
 3. ADDRESS OF OPERATOR
BOX 289, FARMINGTON, NEW MEXICO
 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
 AT SURFACE: 1550'S, 1500'W
 AT TOP PROD. INTERVAL:
 AT TOTAL DEPTH:
 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE
SF 078389
 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
 7. UNIT AGREEMENT NAME
 8. FARM OR LEASE NAME
LUCERNE A
 9. WELL NO.
8
 10. FIELD OR WILDCAT NAME
BLANCO PC
 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
SEC. 9, T-31-N, R-10-W
NMPM
 12. COUNTY OR PARISH
San Juan
 13. STATE
New Mexico
 14. API NO.
 15. ELEVATIONS (SHOW DF, KDB, AND WD)
6142' GL

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:
 TEST WATER SHUT-OFF ☐ ☒
 FRACTURE TREAT ☐ ☒
 SHOOT OR ACIDIZE ☐ ☐
 REPAIR WELL ☐ ☐
 PULL OR ALTER CASING ☐ ☐
 MULTIPLE COMPLETE ☐ ☐
 CHANGE ZONES ☐ ☐
 ABANDON* ☐ ☐
 (other) _____

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4/2/78: T.D. 3147'. Ran 99 joints 2 7/8", 6.5# CW-55 production casing, 3135' set at 3147'. Baffle set at 3136'. Cemented with 570 cu. ft. cement. WOC 18 hours. Top of cement at 2950'.

6/24/78: Pressure tested casing to 4000#, OK. Shot 2 squeeze holes at 2940 and 2972 and squeezed w/100 sks of cement. Did not hold. Squeezed w/100 sks cement. Did not hold. Re-squeezed w/100 sks cement. Held OK.

8/25/78: Tested casing to 4000#, OK. PBTD 3136'. Perfed 2947, 2953, 2959, 2979, 2985, 2988, 2998, 3032 with 1 SPZ. Fraced w/46,000# 10/20 sand and 44,900 gal. slick water. Flushed w/1092 gals. water.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED N. D. Buice TITLE Drilling Clerk DATE 11/10/78

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
 CONDITIONS OF APPROVAL, IF ANY: