200

 $\mathbb{C}[X] \times \mathbb{C}^{n}$

5. LEASE

UNITED STATES DEPARTMENT OF THE INTERIOR

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF	DEPARTMENT OF THE INTERIOR	NM 0607
SUNDRY NOTICES AND REPORTS ON WELLS (CO. not use this form for proposals to drill for to deepen or plug back to a different eservoir. Use Form 9-312- Gro such proposals.) 7. UNIT AGREEMENT NAME 7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME ATLANTIC C 9. WELL NO. 2A. 10. FIELD OR WILDCAT NAME BLANCO M. V. 11. SEC. T. R., M., OR BLK. AND SURVEY AREA SEC. 35, T-31-N, R-1 below.) AT SURFACE: 920'S, 1930'E AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF RRACTURE TREAT SHOOT OR ACIDIZE REPAR WELL MULTIPLE COMPLETE CHANGE ZONES BABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent daincluding estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations measured and true vertical depths for all markers and zones pertinent to this work.)* 3/8/78: Spudded well. Drilled surface hole. Ran 5 jts. 9 5/8", 36# K-55 surface casing 206' set at 218'. Ceme with 295 cu. ft. cement. Circulated to surface. WOC 12 hours; he 600#/30 minutes.	GEOLOGICAL SURVEY	
NUMBRY NOTICES AND REPORT OF PROPOSED to delige to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.) 1. oil	CUNDOV NOTICES AND DEPORTS ON WELLS	
1. oil gas Sas Other 2. NAME OF OPERATOR EL PASO NATURAL GAS CO. 3. ADDRESS OF OPERATOR BOX 990, FARMINGTON, NEW MEXICO 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below) AT SURFACE: 920'S, 1930'E AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: REST WATER SHUT-OFF ERRACTURE TREAT SHOT OR ACIDIZE BEPAIR WELL UPLL OR ALTER CASING WILLIPLE COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent defaincluding estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations measured and true vertical depths for all markers and zones pertinent to this work.)* 3/8/78: Spudded well. Drilled surface hole. Ran 5 jts. 9 5/8", 36# K-55 surface casing 206' set at 218'. Cemer with 295 cu. ft. cement. Circulated to surface. WOC 12 hours; he 600#/30 minutes.		
Well Well A other 2. NAME OF OPERATOR EL PASO NATURAL GAS CO. 3. ADDRESS OF OPERATOR BOX 990, FARMINGTON, NEW MEXICO 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SUBFACE: 920'S, 1930'E AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: REST WATER SHUT-OFF SHOOT OR ACIDIZE BHOOT OR ACIDIZE BANDON' BOOT OR ACIDIZE BHOOT OR ACIDIZE BANDON' BOOT OR ACIDIZE BHOOT OR ACIDIZE BANDON' BOOT OR ACIDIZE BANDON' BHOTT OR ACIDIZE BIOT OR ACIDIZE BANDON' BOOT OR ACIDIZE BANDON' BHOT	Do not use this form for proposals to drill or to deepen or plug back to a different eservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
well well wother 2. NAME OF OPERATOR EL PASO NATURAL GAS CO. 3. ADDRESS OF OPERATOR BOX 990, FARNINGTON, NEW MEXICO 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SUBFACE: 920'S, 1930'E AT TOP PROD. INTERVAL: AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: REST WATER SHUT-OFF SHOOT OR ACIDIZE REPAIR WELL UPLL OR ALTER CASING MULTIPLE COMPLETE DHANGE ZONES BABANDON* fother) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent data including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations measured and true vertical depths for all markers and zones pertinent to this work.)* 3/8/78: Spudded well. Drilled surface hole. Ran 5 jts. 9 5/8", 36# K-55 surface casing 206' set at 218'. Ceme. With 295 cu. ft. cement. Circulated to surface. WOC 12 hours; he 600#/30 minutes.	1 oil gas cr	ATLANTIC C
EL PASO NATURAL GAS CO. 3. ADDRESS OF OPERATOR BOX 990, FARMINGTON, NEW MEXICO 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 920'S, 1930'E AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF RACTURE TREAT CASING NULTIPLE COMPLETE COMPLETE COMPLETE CHANGE ZONES MULTIPLE COMPLETE COMPLETE COMPLETE OPERATIONS (Clearly state all pertinent details, and give pertinent do including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations measured and true vertical depths for all markers and zones pertinent to this work.)* 3/8/78: Spudded well. Drilled surface hole. Ran 5 jts. 9 5/8", 36# K-55 surface casing 206' set at 218'. Cemewith 295 cu. ft. cement. Circulated to surface. WOC 12 hours; he 600#/30 minutes. Subsurface Safety Valve: Manu. and Type Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct	" =	
3. ADDRESS OF OPERATOR BOX 990, FARMINGTON, NEW MEXICO 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 920'S, 1930'E AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: EST WATER SHUT-OFF RACTURE TREAT HIGHOOT OR ACIDIZE REPAIR WELL VILL OR ALTER CASING UNLITIPLE COMPLETE BANDON* other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent da including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations measured and true vertical depths for all markers and 2 ones pertinent to this work.)* 3/8/78: Spudded well. Drilled surface hole. Ran 5 jts. 9 5/8", 36# K-55 surface casing 206' set at 218'. Cemer with 295 cu. ft. cement. Circulated to surface. WOC 12 hours; he 600#/30 minutes.	2. NAME OF OPERATOR	2A 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
BOX 990, FARMINGTON, NEW MEXICO 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below) AT SURFACE: 920'S, 1930'E AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF SHOOT OR ACIDIZE SHOOT OR ALTER CASING SHOOT OR ALTER CASING SHOOT OR SHOOT OR ALTER CASING SHOOT OR SHOOT OR SHOOT OR SHOOT OR SHOOT OR ALTER CASING SHOOT OR	EL PASO NATURAL GAS CO.	— [
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 920'S, 1930'E AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: EST WATER SHUT-OFF RACTURE TREAT DULL OR ALTER CASING MULTIPLE COMPLETE BHANDON* Other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent do including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations measured and true vertical depths for all markers and zones pertinent to this work.)* 3/8/78: Spudded well. Drilled surface hole. Ran 5 jts. 9 5/8", 36# K-55 surface casing 206' set at 218'. Ceme: with 295 cu. ft. cement. Circulated to surface. WOC 12 hours; he 600#/30 minutes.		
Delow.) AT SURFACE: 920'S, 1930'E AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 17. REST WATER SHUT-OFF 18. STATE SAN JUAN 19. SUBSEQUENT REPORT OF: 19. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT OF: 19. CHECK APPROVAL TO: SUBSEQUENT REPORT OF: 19. CHARGE TREAT 19. CHECK APPROVAL TO: SUBSEQUENT REPORT OF: 19. CHARGE TREAT 19. CHARGE TREAT 19. CHARGE CASING CHARGE CASING CHARGE CASING COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent details.) 19. CHARGE TORS 19. CHARGE TO		
AT SUFFACE: 920'S, 1930'E AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: EST WATER SHUT-OFF	•	1
AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: EST WATER SHUT-OFF		
AT TOTAL DEFTH: 6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 15. ELEVATIONS (SHOW DF, KDB, AND M 6474 ' GL 15. ELEVATIONS (SHOW DF, KDB, AND M 6474 ' GL 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT TO INDICATE SHOW THE APPROPRIATE OF NOTICE SHOW THE APPROP		_
6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: SET WATER SHUT-OFF RACTURE TREAT SHOTO OF SUBSEQUENT REPORT OF: SET WATER SHUT-OFF SHOTO OF SUBSEQUENT REPORT OF: SEPAIR WELL SUBSEQUENT REPORT OF: SET WATER SHUT-OFF SUBSEQUENT REPORT OF: SET WATER SHOTON SUBSEQUENT SHOTO	AT TOTAL DEPTH:	
REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: REST WATER SHUT-OFF	6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE.	
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: Comparison		15. ELEVATIONS (SHOW DF, KDB, AND WD)
EST WATER SHUT-OFF		
RACTURE TREAT HOOT OR ACIDIZE CEPAIR WELL ULL OR ALTER CASING MULTIPLE COMPLETE HANGE ZONES BBANDON* other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent daincluding estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations measured and true vertical depths for all markers and zones pertinent to this work.)* 3/8/78: Spudded well. Drilled surface hole. Ran 5 jts. 9 5/8", 36# K-55 surface casing 206' set at 218'. Cemewith 295 cu. ft. cement. Circulated to surface. WOC 12 hours; he 600#/30 minutes.		
Subsurface Safety Valve: Manu. and Type SEPAIR WELL (NOTE: Report results of multiple completion or change on Form 9-330.) (NOTE: Report results of multiple completion or change on Form 9-330.) (NOTE: Report results of multiple completion or change on Form 9-330.) (NOTE: Report results of multiple completion or change on Form 9-330.) (NOTE: Report results of multiple completion or change on Form 9-330.) (NOTE: Report results of multiple completion or change on Form 9-330.) (NOTE: Report results of multiple completion or change on Form 9-330.) (NOTE: Report results of multiple completion or change on Form 9-330.) (NOTE: Report results of multiple completion or change on Form 9-330.) (NOTE: Report results of multiple completion or change on Form 9-330.) (NOTE: Report results of multiple completion or change on Form 9-330.) (NOTE: Report results of multiple completion or change on Form 9-330.) (NOTE: Report results of multiple completion or change on Form 9-330.) (NOTE: Report results of multiple completion or change on Form 9-330.) (NOTE: Report results of multiple completion or change on Form 9-330.) (NOTE: Report results of multiple completion or change on Form 9-330.) (NOTE: Report results of multiple completion or change on Form 9-330.) (NOTE: Report results of multiple completion or change on Form 9-330.) (NOTE: Report results of multiple completion or change on Form 9-330.) (NOTE: Report results of multiple completion or change on Form 9-330.) (NOTE: Report results of multiple change on Form 9-330.) (NOTE: Report results of multiple change on Form 9-330.) (NOTE: Report results of multiple change on Form 9-330.) (NOTE: Report results of multiple change on Form 9-330.) (NOTE: Report results of multiple change on Form 9-330.) (NOTE: Report results of multiple change on Form 9-330.) (NOTE: Report results of multiple change on Form 9-330.) (NOTE: Report results of multiple change on Form 9-330.) (NOTE: Report results of multiple change on Form 9-330.) (NOTE: Report results of multi		
COLUMB Complete Change on Form 9-330.) Complete Change on Form 9-330.) Change of Change of Change on Form 9-330.} Change of Cha		
MULTIPLE COMPLETE		(NOTE: Report results of multiple completion or zone
#HANGE ZONES		change on Form 9-330.)
DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent data including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations measured and true vertical depths for all markers and zones pertinent to this work.)* 3/8/78: Spudded well. Drilled surface hole. Ran 5 jts. 9 5/8", 36# K-55 surface casing 206' set at 218'. Cemer with 295 cu. ft. cement. Circulated to surface. WOC 12 hours; he 600#/30 minutes.		
Other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent data including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations measured and true vertical depths for all markers and zones pertinent to this work.)* 3/8/78: Spudded well. Drilled surface hole. Ran 5 jts. 9 5/8", 36# K-55 surface casing 206' set at 218'. Cemewith 295 cu. ft. cement. Circulated to surface. WOC 12 hours; he 600#/30 minutes. Subsurface Safety Valve: Manu. and Type		
including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations measured and true vertical depths for all markers and zones pertinent to this work.)* 3/8/78: Spudded well. Drilled surface hole. Ran 5 jts. 9 5/8", 36# K-55 surface casing 206' set at 218'. Cemewith 295 cu. ft. cement. Circulated to surface. WOC 12 hours; he 600#/30 minutes. Subsurface Safety Valve: Manu. and Type		
Ran 5 jts. 9 5/8", 36# K-55 surface casing 206' set at 218'. Ceme with 295 cu. ft. cement. Circulated to surface. WOC 12 hours; he 600#/30 minutes. Subsurface Safety Valve: Manu. and Type	including estimated date of starting any proposed work. If well is	directionally drilled, give subsurface locations and
Ran 5 jts. 9 5/8", 36# K-55 surface casing 206' set at 218'. Ceme with 295 cu. ft. cement. Circulated to surface. WOC 12 hours; he 600#/30 minutes. Subsurface Safety Valve: Manu. and Type		
Ran 5 jts. 9 5/8", 36# K-55 surface casing 206' set at 218'. Ceme with 295 cu. ft. cement. Circulated to surface. WOC 12 hours; he 600#/30 minutes. Subsurface Safety Valve: Manu. and Type		
with 295 cu. ft. cement. Circulated to surface. WOC 12 hours; he 600#/30 minutes. Subsurface Safety Valve: Manu. and Type	3/8/78: Spudded well. Drilled surface hole.	、現場で Annual Company Company Company Company
Subsurface Safety Valve: Manu. and Type Set @	with 295 cu. ft. cement. Circulated	
Subsurface Safety Valve: Manu. and Type Set @		
Subsurface Safety Valve: Manu. and Type Set @		10 10 10 10 10 10 10 10 10 10 10 10 10 1
18. I hereby certify that the foregoing is true and correct	Subcurface Safety Valve: Manu, and Type	
		The second secon
SIGNED V. W. LHICE TITLE Drilling Clerk DATE 3/13/78	1/9/2	
3/13/10	SIGNED V. P. JUSED TITLE Drilling Cl	erk DATE3/13/78
(This space for Federal or State office use)	(This space for Federal or State o	ffice use)
APPROVED BY DATE	APPROVED BY TITLE	DATE