## UNITED STATES DEPARTMENT OF THE INTERIOR SUBMIT IN TRIPLICATE\* (Other Instructions on reverse side)

Dakota Sand test (Dryhole).

reservoir.

Form approved. Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO.

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

GEOLOGICAL SURVEY

Sec.13 - T31N - R16W

	SUND	RY I	NOTICES	AND	REPOR	TS	ON	WELLS	ò
(Do not	use this fo	rm for Use "Al	proposals to	drill or to	deepen or	plug such j	back to	a differer s.)	at

Robert C. Anderson

5929 N. May Ave. Oklahoma City, Oklahoma 73112

4. DOCATION OF WELL: Report location clearly and in accordance with any State requirements
See also space 17 below: 790' FWL - 1850' FNL

ADDRESS OF OPERATOR The Summit Bldg. - Suite 411

Ute Mtn. Ute

M-00-C-1420-1933

7. UNIT AGREEMENT NAME

None

8. FARM OR LEASE NAME

UTE TRIBE

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

Straight Canyon D**a**kota

11. SEC., T., B., M., OR BLK. AND SURVEY OR AREA
Sec.13- T31N - R16W N.M.P.M.

12. COUNTY OR PARISH 13. STATE

San Juan

14. PERMIT NO.

NAME OF OPERATOR

15. ELEVATIONS (Show whether DF, RT, GE, etc.)

5754.5 KB 5750 GR

## Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:				SUBSEQUENT REPORT OF:			
			1 113				
TEST WATER SHUT-OFF		Parti OR AUTER CASING		WATER SHUT OFF	REPAIRING WELL		
FRACTURE TREAT		SECURIBLE COMPLETE		FRACTURE TREATMENT	ALTERING CASING		
SHOOT OR ACIDIZE		ABANDON*	X	SHOOTING OR ACIDIZING	ABANDON MENT*		
REPAIR WELL		CHANGE PLANS		(Other)			
(Other)			<u> </u>	(Note: Report results of mu Completion or Recompletion 1	Itiple completion on Well Report and Log form.)		

17. b. Scribe proposed or comparting operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drifted, give subsurface locations and measured and true vertical depths for all markers and zones pertiproposed work. If well is directionally drilled, give subsurvate locations and the state and found to indicate the state and found to indicate the state of the s

non-commercial productivity; therefore, it is proposed that the well be abandoned in the following manner and according to previously received instructions as follows:

- (Across Dakota). 1). 100' sement plug 2394 up to 2294
- (Across Gallup sand). 2). 150' cement plug 1830 up to 1680
- 3) a 100 to cement plug 635 up to 5351 across base of surface (50' in & 50' below)
- 30' plug at surface & dryhole marker.

Surface area will be cleaned and re-habilitated as prescribed

It is proposed that this work commence at the earliest rig

availability.

Attow the reby certify that the foregoing	12	L.S.	' _ £	7
Malon	10		eren.	<b>X</b> 9
I hereby certify that the foregoing	is	crue and	correct /	* /

SIGNED Ashton B. Geren, Jr.

TITLE Agent for: Robert C. Anderson

DATE August 3, 1980

-1, ,M-

AUG 1 1 1980

CARL A. BARRICK <del>fine-district</del> engi**neer**  \*See Instructions on Reverse Side

NMOCD