DECEIVED ONCONSERVATION DEVISION

STATE OF NEW MEXICO

ENERGY and MINERALS
DEPARTMENT

This form is not to be used for reporting packer leakage tests in Southeast New Mexico API#

30-045-22838

Page 1 Revised 10/01/78

NORTHWEST MON MENCO PACKER-LEAKAGE TEST

								Well	
erator BURLINGTON RESOURCES OIL & GAS CO.				Lease	PATTERSON	COM		No. <u>1R</u>	
	Unit C Sect	02 Twp.	031N ¹	Rge.	012W	County	SAN JUAN		
		RESERVOIR OR POOL		TY	PE OF PROD.	METH	OD OF PROD.	PROD. MEDIUM	
					(Oil or Gas)	(Flov	w or Art. Lift)	(Tbg. or Csg.)	
Upper Completion	PICTURED CLIFFS				Gas		Flow	Tubing	
Lower Completion	MESAVERDE				Gas	Flow		Tubing	
		PRE-FI	OW SHUT-IN						
Upper	Hour, date shut-in Length of time shut-in			SI press. psig		Stabilized? (Yes or No)			
Completion	9/17/99	144 Hou	rs		528				
Lower Completion	9/17/99	192 Hou			318				
			FLOW TEST	T NO.			-		
Commenced	at (hour,date)* 9/23/99			Zone producing		(Upper or	Lower) UF	PER	
TIME	LAPSED TIME	PRESS			PROD. ZONE		DE14: DY/G		
(hour,date)	SINCE*	Upper Completion	Lower Comple	tion	ТЕМР	RE		MARKS	
9/24/99	168 Hours	366	322						
9/25/99	192 Hours	330	328						
			<u> </u>			-			
roduction rate	during test								
oil:	BOPD based on Bbls. in			Hours.		Grav.	Grav GOR		
	•								
as:		MCFPD; Tested thru (0	Orifice or Meter)): 					
		MID.	rest shut-in	PRESS	URE DATA				
T I	MID-TEST SHUT-IN PRESSURE DATA Description						Stabilized? (Yes or No)	
Upper Completion	noul, date shut-in	Zongai or mine shar-	ign of time situe-th			F I0			
Lower Completion	Hour, date shut-in	Length of time shut-in		SI press. psig		Stabilized? (Yes or No)			

			FLOW TEST NO.	2					
Commenced at (hour, o	date)**		z	Zone producing (Upper or Lower):					
TIME (hour, date)	LAPSED TIME SINCE **	PRESSURE Upper Completion Lower Completio		PROD. ZONE TEMP.	REMARKS				
		opper completion	Lower Completion						
									
					····				
Production rate du	uring test								
Oil:	BC	PD based on	Bbls. in	Hours	Grav	GOR			
Gas:		MCFPI): Tested thru (Orific	e or Meter):					
Remarks:									
	•								
I hereby certify that	at the information her	ein contained is true	and complete to the	hest of my knowledge					
3-	001	- 2 6 139 9 -		oost of my knowledge	•				
Approved		19	O <u>I</u>	perator Burlingto	n Resources				
	il Conservation Divis		D.	Also 1	Par a				
CRIC	hal signed by oh	ARIJE T. PERIM	Ву	A MARIO L	c oy .				
Ву			Ti	tle <u>Operations As</u>	sociate				
987	TITY OIL & GAS IN	SPECTOR, DIST. 🚜							
Title			Da	Date Friday, October 08, 1999					

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and arnually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Tes No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- desired, or may be requested on wells which have previously shown questionable test data.

 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).