Porm	9 - 331
(Мау	1963)

UNITED STATES UNITED STATES SUBMIT IN TRIPLICATE* Other instructions on reverse side)

Form approved. Budget Bureau No 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO.

6. IF INDIAN, ALLOTTEE OR TEIRE NAME

SF-077652

GEOLOGICAL SURVEY						
SUNDRY	NOTICES	AND	REPORTS	ON	WELLS	

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals.) 7. UNIT AGREEMENT NAME WELL X WSLL OTHER

2. NAME OF OPERATOR 8. FARM OR LEASE NAME Southland Royalty Company East 3. ADDRESS OF OPERATOR 9. WELL NO. P. O. Drawer 570, Harmington, New Mexico #22-A 10. FIELD AND POOL, OR WILDCAP

LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below)
At surface 1700' FSL & 880' FEL

Blanco Mesa Verde 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

14. PERMIT NO. 16. BLEVATIONS (Show whether DF, RT, GR, etc.) 5963' GL

Section 26, T31N, R12W 12. COUNTY OR PARISH | 13. STATE San Juan New Mexico

16.


Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO: TEST WATER SHUT-OUR COLOGARIES CASING WATER SHUL-CEF REPAIRING WELL FRACTURE TREAT MULTIPLE COMPLETE FRACTURE TREATMENT ALTERING CASING SHOOT OR ACIDIZE ABANDON* SHOOTING OR ACIDIZING ABANDONMENT* Casing Report REPAIR WELL CHANGE PLANS (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) (Other)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5-01-78 Ran 68 joints of 7", 20#, K-55, 8rd casing landed at 2685'. Cemented with 165 sxs 50/50 Class "B" Poz with 6% gel followed by 70 sacks Class "B" cement with 2% CaCl₂. Plug down at 6:50 PM 5-1-78.

5-04-78 Ran 60 joints of 4-1/2", 10.5#, K-55, 8rd casing set from 2535'-5081' Cemented with 270 sacks 50/50 Class "B" Poz with 6% gel, 1/4# gel flake per sack and 0.6% Halad 9. Plug down at 2:20 PM 5-4-78.



18. I hereby certify that the foregoing is true and correct		· .
	THILE District Production Manager	DATE May 5, 1978
(This space for Federal or State office as's)		
APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	TITLE	DATE