							/	
Form 9-331 (May 1963)	UNITED STATES SUBMIT IN TRIPLICA DEPARTMENT OF THE INTERIOR Verse side) GEOLOGICAL SURVEY			re- 5. LEA	Form approved. Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL 300. NM-01614			
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT-" for such proposals.)						6. IF INDIAN, ALLOTTEE OR THISS NAME		
1. OIL CAS X OTHER						7. UNIT AGREEMENT NAME		
2. NAME OF OPERATOR						8. FARM OR LEASS NAME		
Southland Royalty Company						Thompson		
3. ADDRESS OF OPERATOR						9. WELL NO.		
P. O. Drawer 570, Farmington, New Mexico						#10-A		
 LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 					10. FIF	10. FIELD AND POOL, OR WILDCAT		
1190' FNL & 850' FEL					11. 58	Blanco Mesa Verde 11. SEC., T., R., M., OR BLK. AND SUZVEY OR ASZA		
					S	ection 27,	. T31N.	. R12W
14. PERMIT NO.		15. ELEVATIONS (Sho	w whether DF, RT, C	R, etc.)		UNTY OR PARISH		
			6124' GL		<u> </u> s	an Juan	New 1	lexico
16.	Check A	opropriate Box To	Indicate Natur	e of Notice, Report, o	r Other Do	ata		
NOTICE OF INTENTION TO:				SUBSEQUENT REPORT OF:				
TEST WATER SH	UT-OFF	PULL OR ALTER CASING		WATEB SHUT-OFF		REPAIRING W	ELL	7
FRACTURE TREAT	c	MULTIPLE COMPLETE		FRACTURE TREATMENT		ALTERING CA	SING	-
SHOOT OR ACIDI	ZE	ABANDON*		SHOOTING OR ACIDIZING		ABANDONMEN		-
REPAIR WELL		CHANGE PLANS		(Other) <u>Ca</u>	sing Re	port	X	-
(Other)				(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)				
17. DESCRIBE PROPOS proposed work nent to this wo	. IL WEB 15 ULLECLE	CRATIONS (Clearly state onally drilled, give sub	all pertinent det: surface locations	ails, and give pertinent dat and measured and true ver	and Includin		·····	ig any perti-

- 5-08-78 Ran 93 joints of 7", 20#, K-55, 8rd casing landed at 2854'. Cemented with 160 sacks 50/50 Class "B" Poz with 6% gel followed by 70 sacks Class "B" cement and 2% CaCl. Plug down at 9:00 PM 5-8-78.
- 5-12-78 Ran 62 joints of 4-1/2", 10.5#, K-55, 8rd casing set from 2677'-5284'. Cemented with 320 sacks 50/50 Class "B" Poz with 6% gel, 1/4# gel flake per sack and 0.6% Halad 9. Plug down at 10:15 AM 5-12-78.

		ECEIVED
		MAY 17 1978
15. I become certify that the foregoing is true and correct SIGNED	TITLE District Production Manager	DATE May 16, 1978
(This space for Federal or State office use)		
APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	TITLE	DATE