

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Form Approved.  
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐

2. NAME OF OPERATOR  
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR  
P.O. Box 289, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1820'S, 1100'E  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE  
NM 013688

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Atlantic

9. WELL NO.  
1A

10. FIELD OR WILDCAT NAME  
Blanco M.V.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 25, T-31-N, R-10-W  
N.M.P.M.

12. COUNTY OR PARISH  
San Juan

13. STATE  
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6624' GL

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐ ☒

FRACTURE TREAT ☐ ☒

SHOOT OR ACIDIZE ☐ ☐

REPAIR WELL ☐ ☐

PULL OR ALTER CASING ☐ ☐

MULTIPLE COMPLETE ☐ ☐

CHANGE ZONES ☐ ☐

ABANDON\* ☐ ☐

(other) ☐ ☐

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

11-03-78: TD 3811'. Ran 93 jts. 7", 20#, K-55 intermediate casing, 3800' set at 3811'. Cemented w/389 cu. ft. cement. WOC 12 hours; held 1200#/30 minutes. Top of cement at 2100'.

11-06-78: TD 6069'. Ran 75 jts. 4 1/2", 10.5#, K-55 casing liner, 2441' set 3628-6069'. Float collar set at 6052'. Cemented w/424 cu. ft. cement. WOC 18 hours.

04-29-79: PBTD 6052'. Tested casing to 3500#, OK. Perfed Mass. & Lower P.L. 5607, 5613, 5636, 5641, 5646, 5651, 5683, 5688, 5693, 5698, 5717, 5736, 5742, 5748, 5782, 5789, 5818, 5866, 5895, 5904, 5940, 5957, 6039' w/1 SPZ. Fraced w/67,000# 20/40 sand and 134,000 gal. water. Flushed w/7812 gal. water. Perfed C.H. & Men. 4932, 5061, 5159, 5167, 5175, 5183, 5197, 5204, 5212, 5217, 5233, 5264, 5292, 5358, 5367, 5385, 5474, 5482, 5490, 5498, 5546, 5554, 5562' w/1 SPZ. Fraced w/81,000# 20/40 sand and 162,000 gal. water. Flushed w/7434 gal. water.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct


SIGNED M. P. Busco TITLE Drilling Clerk DATE April 30, 1979

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.



*mmice*