

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐  
well well

2. NAME OF OPERATOR  
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR  
P.O. Box 289, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1700'S, 1840'E  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

☒  
☒  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE  
NM 0606

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Atlantic A

9. WELL NO.  
5A

10. FIELD OR WILDCAT NAME  
Blanco M.V.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 26, T-31-N, R-10-W  
N.M.P.M.

12. COUNTY OR PARISH  
San Juan

13. STATE  
New Mexico

14. API NO.

15. ELEVATIONS. (SHOW DF, KDB, AND WD)  
6329' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1-03-79: TD 3429'. Ran 85 jts. 7", 20#, K-55 intermediate casing, 3417' set at 3429'. Cemented w/385 cu. ft. cement. WOC 12 hours; held 1200#/30 minutes. Top of cement at 1975'.

1-07-79: TD 5750'. Ran 76 jts. 4 1/2", 10.5#, K-55 casing liner, 2490' set 3260'-5750'. Float collar set at 5732'. Cemented w/431 cu. ft. cement. WOC 18 hours.

5-24-79: PBTD 5732'. Tested casing to 3500#, OK. Perfed Upper & Lower PE 5159, 5180, 5191, 5195, 5359, 5363, 5367, 5371, 5389, 5392, 5416, 5420, 5424, 5428, 5446, 5450, 5464, 5510, 5547, 5601, 5636, 5670, 5718' w/1 SPZ. Fraced w/57,000# 20/40 sand and 114,000 gal. water. Flushed w/7173 gal. water. Perfed Men. & C.H. 4628, 4675, 4723, 4746, 4765, 4780, 4844, 4870, 4876, 4882, 4888, 4894, 4903, 4913, 4927, 4932, 4939, 5036, 5052' w/1 SPZ. Fraced w/55,500# 20/40 sand and 111,000 gal. water. Flushed w/6400 gal. water.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.


18. I hereby certify that the foregoing is true and correct

SIGNED J. P. Brisco TITLE Drilling Clerk DATE May 25, 1979

(This space for Federal or State office)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

RECEIVED  
MAY 25 1979  
U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.



\*See Instructions on Reverse Side.

NMOCC