UNITED STATES	Budget Bureau No. 42–R1424 5. LEASE Top To
DEPARTMENT OF THE INTERIOR	5. LEASE
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas X other	Atlantic A
	9. WELL NO.
2. NAME OF OPERATOR	1A 39 10. FIELD OR WILDCAT NAME
El Paso Natural Gas Company 3. ADDRESS OF OPERATOR	Blanco M.V.
P.O. Box 289, Farmington, N.M. 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	AREA Sec. 27, T-31-N, R-10-W
AT SURFACE: 1550' S, 1650' E	N. M. P. M. 12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL:	San Juan 20 ct New Mexico
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	
	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6230' G. L.
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	
SHOOT OR ACIDIZE	
REPAIR WELL PULL OR ALTER CASING	(NOTE: Report results of multiple completion or zone change on Form 9-330.)
CHANGE ZONES	A chairte an
(other)	
6-5-79: PBTD 5608'. Tested csg. to 3500#, 0 5202,5210,5218,5224,5230,5240,5244,5	K. Perfed Mass. P.L. 5186,5194, 268 5276 5292 5297 5321 5327 5339
5359,5388,5411,5440,5459,5499,5545,5 93 000# 20/40 sand and 186 000 gal	571,5616' w/1 SPZ. Fraced w/
93,000# 20/40 sand and 186,000 gal.	571,5616' w/1 SPZ. Fraced w/ water. Flushed w/ 7014 gal, wtr.
93,000# 20/40 sand and 186,000 gal. 6-6-79: Perfed C.H. and Men. 4485,4533,4620, 4738,4744,4750,4769,4780,4788,4796,4	571,5616' w/1 SPZ. Fraced w/ water. Flushed w/ 7014 gal. wtr. 4637,4705,4714,4720,4726,4732, 800,4880,4884,4932,4937,5067'
93,000# 20/40 sand and 186,000 gal. 6-6-79: Perfed C.H. and Men. 4485,4533,4620, 4738,4744,4750,4769,4780,4788,4796,4 w/ 1 SPZ. Fraced w/ 65,000# 20/40 s	571,5616' w/1 SPZ. Fraced w/ water. Flushed w/ 7014 gal. wtr. 4637,4705,4714,4720,4726,4732, 800,4880,4884,4932,4937,5067'
93,000# 20/40 sand and 186,000 gal. 6-6-79: Perfed C.H. and Men. 4485,4533,4620, 4738,4744,4750,4769,4780,4788,4796,4	571,5616' w/1 SPZ. Fraced w/ water. Flushed w/ 7014 gal. wtr. 4637,4705,4714,4720,4726,4732, 800,4880,4884,4932,4937,5067'
93,000# 20/40 sand and 186,000 gal. 6-6-79: Perfed C.H. and Men. 4485,4533,4620, 4738,4744,4750,4769,4780,4788,4796,4 w/ 1 SPZ. Fraced w/ 65,000# 20/40 s	571,5616' w/1 SPZ. Fraced w/ water. Flushed w/ 7014 gal. wtr. 4637,4705,4714,4720,4726,4732, 800,4880,4884,4932,4937,5067'
93,000# 20/40 sand and 186,000 gal. 6-6-79: Perfed C.H. and Men. 4485,4533,4620, 4738,4744,4750,4769,4780,4788,4796,4 w/ 1 SPZ. Fraced w/ 65,000# 20/40 s Flushed w/ 6636 gal. water.	571,5616' w/1 SPZ. Fraced w/ water. Flushed w/ 7014 gal. wtr. 4637,4705,4714,4720,4726,4732, 800,4880,4884,4932,4937,5067'
93,000# 20/40 sand and 186,000 gal. 6-6-79: Perfed C.H. and Men. 4485,4533,4620, 4738,4744,4750,4769,4780,4788,4796,4 w/ 1 SPZ. Fraced w/ 65,000# 20/40 s Flushed w/ 6636 gal. water.	571,5616' w/1 SPZ. Fraced w/ water. Flushed w/ 7014 gal. wtr. 4637,4705,4714,4720,4726,4732, 800,4880,4884,4932,4937,5067'
 93,000# 20/40 sand and 186,000 gal. 6-6-79: Perfed C.H. and Men. 4485,4533,4620, 4738,4744,4750,4769,4780,4788,4796,4 w/ 1 SPZ. Fraced w/ 65,000# 20/40 s Flushed w/ 6636 gal. water. Subsurface Safety Valve: Manu. and Type	571,5616' w/1 SPZ. Fraced w/ water. Flushed w/ 7014 gal. wtr. 4637,4705,4714,4720,4726,4732, 800,4880,4884,4932,4937,5067' and and 130,000 gal. waters Set 6 JUN 12
93,000# 20/40 sand and 186,000 gal. 6-6-79: Perfed C.H. and Men. 4485,4533,4620, 4738,4744,4750,4769,4780,4788,4796,4 w/ 1 SPZ. Fraced w/ 65,000# 20/40 s Flushed w/ 6636 gal. water.	571,5616' w/1 SPZ. Fraced w/ water. Flushed w/ 7014 gal. wtr. 4637,4705,4714,4720,4726,4732, 800,4880,4884,4932,4937,5067' and and 130,000 gal. waters Set 6 JUN 12
 93,000# 20/40 sand and 186,000 gal. 6-6-79: Perfed C.H. and Men. 4485,4533,4620, 4738,4744,4750,4769,4780,4788,4796,4 w/ 1 SPZ. Fraced w/ 65,000# 20/40 s Flushed w/ 6636 gal. water. Subsurface Safety Valve: Manu. and Type	571,5616' w/1 SPZ. Fraced w/ water. Flushed w/ 7014 gal. wtr. 4637,4705,4714,4720,4726,4732, 800,4880,4884,4932,4937,5067' and and 130,000 gal. waters Set a fill for the fill of the fill
93,000# 20/40 sand and 186,000 gal. 6-6-79: Perfed C.H. and Men. 4485,4533,4620, 4738,4744,4750,4769,4780,4788,4796,4 w/ 1 SPZ. Fraced w/ 65,000# 20/40 s Flushed w/ 6636 gal. water. Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED Lange Manual TITLE Drilling Cle	571,5616' w/1 SPZ. Fraced w/ water. Flushed w/ 7014 gal. wtr. 4637,4705,4714,4720,4726,4732, 800,4880,4884,4932,4937,5067' and and 130,000 gal. waters Set a fill for the fill of the fill
93,000# 20/40 sand and 186,000 gal. 6-6-79: Perfed C.H. and Men. 4485,4533,4620, 4738,4744,4750,4769,4780,4788,4796,4 w/ 1 SPZ. Fraced w/ 65,000# 20/40 s Flushed w/ 6636 gal. water. Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED III Drilling Cle (This space for Federal of State of	571,5616' w/1 SPZ. Fraced w/ water. Flushed w/ 7014 gal: wtr. 4637,4705,4714,4720,4726,4732, 800,4880,4884,4932,4937,5067' and and 130,000 gal. waters set of the set
93,000# 20/40 sand and 186,000 gal. 6-6-79: Perfed C.H. and Men. 4485,4533,4620, 4738,4744,4750,4769,4780,4788,4796,4 w/ 1 SPZ. Fraced w/ 65,000# 20/40 s Flushed w/ 6636 gal. water. Subsurface Safety Valve: Manu. and Type	571,5616' w/1 SPZ. Fraced w/ water. Flushed w/ 7014 gal. wtr. 4637,4705,4714,4720,4726,4732, 800,4880,4884,4932,4937,5067' and and 130,000 gal. waters Set 0 JUN 12 Tk DATE 6-1179 DATE 0 DATE 0 California
93,000# 20/40 sand and 186,000 gal. 6-6-79: Perfed C.H. and Men. 4485,4533,4620, 4738,4744,4750,4769,4780,4788,4796,4 w/ 1 SPZ. Fraced w/ 65,000# 20/40 s Flushed w/ 6636 gal. water. Subsurface Safety Valve: Manu. and Type	571,5616' w/1 SPZ. Fraced w/ water. Flushed w/ 7014 gal: wtr. 4637,4705,4714,4720,4726,4732, 800,4880,4884,4932,4937,5067' and and 130,000 gal. waters set of the set
93,000# 20/40 sand and 186,000 gal. 6-6-79: Perfed C.H. and Men. 4485,4533,4620, 4738,4744,4750,4769,4780,4788,4796,4 w/ 1 SPZ. Fraced w/ 65,000# 20/40 s Flushed w/ 6636 gal. water. Subsurface Safety Valve: Manu. and Type	571,5616' w/1 SPZ. Fraced w/ water. Flushed w/ 7014 gal. wtr. 4637,4705,4714,4720,4726,4732, 800,4880,4884,4932,4937,5067' and and 130,000 gal. waters in the second secon
93,000# 20/40 sand and 186,000 gal. 6-6-79: Perfed C.H. and Men. 4485,4533,4620, 4738,4744,4750,4769,4780,4788,4796,4 w/ 1 SPZ. Fraced w/ 65,000# 20/40 s Flushed w/ 6636 gal. water. Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SiGNED	571,5616' w/1 SPZ. Fraced w/ water. Flushed w/ 7014 gal. wtr. 4637,4705,4714,4720,4726,4732, 800,4880,4884,4932,4937,5067' and and 130,000 gal. waters in the second secon

7 3943