

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR
EL PASO NATURAL GAS CO.
3. ADDRESS OF OPERATOR
BOX 289, FARMINGTON, NEW MEXICO
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1750'N, 1480'W
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

- ☒
☒
☐
☐
☐
☐
☐
☐

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4/29/78: T.D. 3248'. Ran 80 joints 7", 20#, K-55 intermediate casing, 3237' set at 3248'. Cemented with 426 cu. ft. cement.

4/30/78: Well blew out. Ran Bond log. Perfed 2 squeeze holes at 2700'. Set RTTS packer at 2420' and re-cemented through squeeze holes w/361 cu. ft. WOC 12 hours, held 1500#/30 minutes. Top of cement at 1450'.

5/5/78: T.D. 5678'. Ran 170 joints 4 1/2", 10.5# K-55 production casing, 5477' set at 5487'. Cemented with 243 cu. ft. cement. WOC 18 hours. Top of cement at 2850'.

(OVER)

Subsurface Safety Valve: Manu. and Type _____ et @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED A. G. Buco TITLE Drilling Clerk DATE 10/17/78

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

N/moc

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

10/13/78: Shot 1 sq. hole at 4700'. Packer set at 4512'. Squeezed with 50 sks cement. Well went on vacuum. Re-squeezed hole at 4700' with 75 sks cement. Well locked up at 3000 psi. Released pkr and reversed cement. WOC. Shot sq. hole at 4350'. Set packer at 4136'. Squeezed with 75 sks cement. Pressure tested OK.

10/14/78: Perfed C.H. and Men. 4510, 4608, 4648, 4655, 4757, 4780, 4803, 4822, 4835, 4840, 4846, 4855, 4872, 4877, 4959, 4996, 5028, 5049, 5055, 5101, 5107 w/1 SPZ. Fraced w/66,000 # 20/40 sand and 116,000 gal. slick water. Flushed w/ 3000 gal. water. Perfed Mass. P.L. 5219, 5225, 5231, 5237, 5244, 5249, 5254, 5264, 5270, 5276, 5282, 5288, 5310, 5332, 5342, 5366, 5389 w/1 SPZ. Fraced w/49,000 # 20/40 sand and 89,000 gal. slick water. Flushed w/3600 gal. water. Fraced lower P.L. open hole; 55,000 # 20/40 sand and 65,000 gal. gelled condensate. Flushed w/ 3600 gal. water.

GPO : 1976 O-214-149