5. LEASE

UNITED STATES PARTMENT OF THE INTERIOR

DEPARTMENT OF THE INTERIOR	NM 0608 75 77 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
	7. UNIT AGREEMENT NAME
SUNDRY NOTICES AND REPORTS ON WELLS	San Juan 32-9 Unit
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil ☐ gas ☑	San Juan 32-9 Unit
well well other	9. WELL NO.
2. NAME OF OPERATOR	13A 44 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4
El Paso Natural Gas Company	10. FIELD OR WILDCAT NAME Blanco M.V.
3. ADDRESS OF OPERATOR P.O. Box 289, Farmington, New Mexico 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA Sec. 14, T-31-N, R-10-W
below.)	N.M.P.M.
AT SURFACE: 1190'S, 1140'E AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE San Juan New Mexico
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	6335' GL
TEST WATER SHUT-OFF	
FRACTURE TREAT	
SHOOT OR ACIDIZE	
REPAIR WELL	(NOTE: Report results of multiple completion or zone change on Form 9–330.)
PULL OR ALTER CASING	
CHANGE ZONES	
ABANDON* □	
(other)	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is a measured and true vertical depths for all markers and zones pertined	firectionally drilled, give subsurface locations and
10-17-78: TD 3527'. Ran 86 jts. 7", 20#, KS i	ntermediate casing, 3517' set at
3527'. Cemented w/634 cu. ft. cement. WOC 12	hours; held 1200#/30 minutes. Top
of cement at 1675'.	
10-23-78: TD 5898'. Ran 68 jts. 4 1/2", 10.5#	, KS casing liner, 2513' set 3385-
5898'. Float collar set at 5881'. Cemented w/	431 cu. ft. cement. WOC 18 hours.
05-07-79: PBTD 5881'. Tested casing to 3500#, 5372,5378,5384,5390,5396,5404,5409,5416,5444,54 5646,5701,5836' w/1 SPZ. Fraced w/68,500# 20/4 Flushed w/7350 gal. water. Perfed C.H. & Men. 4943,4958,4969,4980,4989,5008,5073,5099,5124,52 w/70,000# 20/40 sand and 140,000 gal. water. F	51,5467,5488,5511,5572,5607,5639, 0 sand and 137,000 gal. water. 4656,4750,4779,4792,4877,4896,4926, 02,5222,5261,5291' w/1 SPZ. Fraced lushed w/7350 gal. water.
Subsurface Safety Valve: Manu. and Type	Set @:
18. I hereby certify that the foregoing is true and correct	
SIGNED N. B. Silver TITLE Drilling C1	erk DATE May 8, 1979
(This space for Federal or State office use)	
APPROVED BY TITLE	DATE STATE S
CONDITIONS OF APPROVAL, IF ANY:	21.43 - 24 Min. 34

*See Instructions on Reverse Side