## HNITED STATES

UNITED STATES  DEPARTMENT OF THE INTERIOR	5. LEASE NM 080281	
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE MAME	
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME	
1. oil gas well other	8. FARM OR LEASE NAME NYE FEDERAL 9. WELL NO.	
2. NAME OF OPERATOR SUPRON ENERGY CORPORATION	1-M 10, FIELD OR WILDCAT NAME	
3. ADDRESS OF OPERATOR	Basin Dakota - Blanco Mesaverde	
P.O. Box 808, Farmington, New Mexico 87401  4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 20, T-31N, R-12W N.M.P.M.	
AT SURFACE: 870'/South line & 1015'/East line AT TOP PROD. INTERVAL: Same as above	12. COUNTY OR PARISH 13. STATE San Juan New Mexico	
AT TOTAL DEPTH: Same as above  16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO.	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6027 GR	
REQUEST FOR APPROVAL TO:  SUBSEQUENT REPORT OF:  TEST WATER SHUT-OFF	(NOTE: Report results of multiple completion or zone change on Form 9–330.)	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinent	irectionally drilled, give subsurface locations and	
1. Drill 12-3/4" hole to T.D. of 305 feet R.K.B	•	
2. Run 278 feet (7 Joints) of 8-5/8", 24.0#, K-	55 surface csg. landed @ 299 feet	

- 17
- 1.
- 2.
- 3. Cement with 250 sx. of class "B" cement w/3% CaCl w/1/4# Flo Cel/sx. Plug down at 3:45 P.M. 3/13/80. Cement circulated to surface.
- 4. W.O. cement 11 hours.
- 5. Pressure test surface pipe to 600 P.S.I.G. Pressure held.

Subsurface Safety Valve: Manu. and Ty	pe	Set @	Ft.
18. I hereby certify that the foregoing	<del></del>	COVED	
SIGNED RUDY D. MOLLO	Area Superintendent	Marc. 11, 1980	
	(This space for Federal or State office use)	15 1 S 120W	
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE DATE	OIL CON. C.3	