

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐

2. NAME OF OPERATOR
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR
P.O. Box 289, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1520'S, 880'E
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input checked="" type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input checked="" type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) <input type="checkbox"/>	<input type="checkbox"/>

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11-15-78: TD 3760'. Ran 96 jts. 7", 20#, K-55 intermediate casing, 3748' set at 3760'. Cemented w/529 cu. ft. cement. WOC 12 hours; held 1200#/30 minutes. Top of cement at 3400'.

11-19-78: TD 6085'. Ran 69 jts. 4 1/2", 10.5#, K-55 casing liner, 2520' set 3565-6085'. Float collar set at 6068'. Cemented w/433 cu. ft. cement. WOC 18 hours.

4-03-79: PBTD 6068'. Tested casing to 3500#, OK. Perfed P.L. 5647, 5651, 5655, 5659, 5675, 5678, 5681, 5699, 5702, 5705, 5708, 5745, 5779, 5788, 5810, 5827, 5868, 5874, 5891, 5916, 5922, 5959, 6038, 6044' w/1 SPZ. Fraced w/63,500# 20/40 sand and 127,000 gal. water. Flushed w/7800 gal. water. Perfed C.H. & Men. 4928, 4933, 5056, 5168, 5173, 5195, 5231, 5237, 5243, 5249, 5255, 5270, 5289, 5340, 5360, 5381, 5392, 5420, 5541, 5559, 5565' w/1 SPZ. Fraced w/64,500# 20/40 sand and 129,000 gal. water. Flushed w/7400 gal. water.

Subsurface Safety Valve: Manu. and Type _____

18. I hereby certify that the foregoing is true and correct

SIGNED D. G. Brisco TITLE Drilling Clerk DATE May 4, 1979

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

5. LEASE
NM 013688

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Atlantic

9. WELL NO.
2A

10. FIELD OR WILDCAT NAME
Blanco M.V.

11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA Sec. 24, T-31-N, R-10-W
N.M.P.M.


12. COUNTY OR PARISH
San Juan

13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6608' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)



Yumoc