

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE*

(See other in-
structions on
reverse side)Form approved.
Budget Bureau No. 42-R355.5.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other _____

b. TYPE OF COMPLETION:

NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR. ☐ Other _____

2. NAME OF OPERATOR

Marathon Oil Company

3. ADDRESS OF OPERATOR

P. O. Box 2659, Casper, Wyoming 82602

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface 1800' FNL and 1650' FWL NW/4 SE/4 NW/4 Unit F

At top prod. interval reported below

At total depth

14. PERMIT NO.

DATE ISSUED

5. LEASE DESIGNATION AND SERIAL NO.

NM-021123

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Ohio "D" Government

9. WELL NO.

1-A

10. FIELD AND POOL, OR WILDCAT

Blanco Mesaverde

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA

Sec. 8, T31N, R12W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

15. DATE SPUDDED 5-12-78 16. DATE T.D. REACHED 5-19-78 17. DATE COMPL. (Ready to prod.) 7-26-78 18. ELEVATIONS (DF, RKB, RT, GE, ETC.)* 5913' GL, 5925' KB 19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD 5000' 21. PLUG, BACK T.D., MD & TVD 4957' 22. IF MULTIPLE COMPL., HOW MANY* -- 23. INTERVALS DRILLED BY -- 24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)* 4880'-4885', 4634'-4708' Point Lookout 25. WAS DIRECTIONAL SURVEY MADE No

26. TYPE ELECTRIC AND OTHER LOGS RUN

SNP, DIL, FDC, CBL, Temp. Survey, Caliper Log

27. WAS WELL CORED

No

28. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
9-5/8"	36#	212.00'	13 1/4"	200 Sacks	None
7"	23#	4,550.00'	8-3/4"	450 Sacks	None

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
4 1/2"	4382.50'	5000'	65	None	2-3/8"	4326.49'	None

31. PERFORATION RECORD (Interval, size and number)

4880'-4885' w/3-3/8" Casing Gun
4634'-4708' w/21 shots, 1/ft
(Point Lookout)

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
4880'-4885'	249 bbls., 1% KCl wtr 520,000 SCF, N2, 48,960# Frac Sand
4634'-4708'	455 bbls., 2% KCl wtr, 1,037,400 SCF, N2, 96,800# of frac sand

33.* PRODUCTION

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)					WELL STATUS (Producing or shut-in)	
7-14-78		Flowing					Shut in waiting on connection to sales	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO	
7-26-78	3	3/4"	→	0	502	0	---	
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)		
319 psig	630 psig	→	0	11244	0	---		

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

To be sold to El Paso Natural Gas Company

TEST WITNESSED BY

E. Nelson MOC 103

35. LIST OF ATTACHMENTS

SEP 1 1978

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records.

SIGNED

TITLE District Operations Manager

DATE

8-29-78

*(See Instructions and Spaces for Additional Data on Reverse Side)

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.

Items 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES: SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES				38. GEOLOGIC MARKERS		
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	MEAS. DEPTH	TRUE VERT. DEPTH
Pictured Cliffs	2,217'	3,850'		Pictured Cliffs Cliff House Menefee Point Lookout	2,217'	
Cliff House	3,850'	4,095'			3,850'	
Menefee	4,095'	4,631'			4,095'	
Point Lookout	4,631'	5,000'			4,631'	