UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

	5. LEASE
	SF 078096
	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
-	
	7. UNIT AGREEMENT NAME
	. 2
	8. FARM OR LEASE NAME
	Mudge
	9. WELL NO.
	7A
	10. FIELD OR WILDCAT NAME
	Blanco Mesa Verde
_	11. SEC., T., R., M., OR BLK. AND SURVEY OR
	AREA Sec. 23, T-31-N, R-11-W
	NMPM
	12. COUNTY OR PARISH 13. STATE
	San-Juan New Mexico
_	14. API NO.

SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331—C for such proposals.)	8. FARM OR LEASE NAME
1 oil gas —	Mudge
1. oil gas other	9. WELL NO.
2. NAME OF OPERATOR	7A
EL PASO NATURAL GAS CO.	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Blanco Mesa Verde
BOX 289, FARMINGTON, NEW MEXICO	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA Sec. 23, T-31-N, R-11-W
below.)	NMPM
AT SURFACE: 1140'N 1645'W AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE
AT TOTAL DEPTH:	San-Juan New Mexico
	14. API NO
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	5860' GR
TEST WATER SHUT-OFF	
FRACTURE TREAT	
SHOOT OR ACIDIZE	
REPAIR WELL	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING	change on Form 9-330.)
CHANGE ZONES	
ABANDON*	그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그
(other)	
including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertiner 10/30/78: T.D. 2877'. Ran 74 joints 7", set at 2877'. Cemented with 442 cu. ft. of 30 minutes. Top of cement at 900'. 11/2/78: T.D. 5182'. Ran 70 joints 4 1/2 2480' set 2702-5182'. Float collar set at ft.cement. WOC 18 hours. 12/18/78: PBTD 5166'. Tested casing to 3 4769,4789,4795,4801,4815,4821,4827,4842,48	20#, KS intermediate casing, 2865' tement. WOC 12 hours, held 1200#/ 2#, 10.5#, KS casing liner, 5166'. Cemented with 426 cu.
4974,5034,5041,5064,5075,5120 with 1 SPZ. 176,904 gal. water. Subsurface Safety Valve: Manu. and Type	Fraced w/72,000# 20/40 sand and
Subsurface Safety Valve: Manu. and Type	
18. I hereby certify that the foregoing is true and correct	1/2/79
SIGNED AV. JO. MAGO TITLE Drilling Cler	DATE ITOTIS
(This space for Federal or State of	
APPROVED BY TITLE	DATE
CONDITIONS OF APPROVAL, IF ANY:	

*See Instructions on Reverse Side



